




3 Warm White LED (3000K)	CRI 80	
	22W	28W
Lumen Output	2900 lm	3560 lm
LOR	0.87	0.87
CRI	80	80
Total Power	24.6W	31.4W
Power Factor	0.97	0.97
Running Current	0.11A	0.14A
Inrush Current	9A (40us)	9A (40us)
Efficacy	102 lm/W	98 lm/W
Emergency Output (BLF)	N/A	N/A

4 Neutral White LED (4000K)	CRI 80	
	22W	28W
Lumen Output	3240 lm	3960 lm
LOR	0.87	0.87
CRI	80	80
Total Power	24.6W	31.4W
Power Factor	0.97	0.97
Running Current	0.11A	0.14A
Inrush Current	9A (40us)	9A (40us)
Efficacy	114 lm/W	109 lm/W
Emergency Output (BLF)	N/A	N/A




SkyWay Indirect

1200mm Modules



LED

22W	LED	1200mm	SW354	LED	22	361
28W	LED	1200mm	SW354	LED	28	361



330V
50Hz

IP
20

7.0 kg

- Zhaga Book 7 LED
- Available in a choice of lumen outputs, delivering up to 3960 lumens
- Efficacies up to 114 lm/W
- Slim profile seamlessly integrating style, performance and function
- Life expectancy in excess of 60,000 hours (L70 B10)
- Colour stability within 3 MacAdams
- Seven wire 16A harness with pushfit terminals fitted as standard to every module
- Indirect Modules cannot be Emergency

Gear types F & G must be operated through a DSI

- A Integral Driver
- F Digital Dim
- J Switch Dim
- S DALI Dim

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)

Tel: (0191) 280 9911 Email: technical@hacel.co.uk Web: www.hacel.co.uk