

230V 50Hz **IP** 20  $\varnothing$  50mm 3.7 kg



	CRI 80	8W	12W	17W
<b>3 Warm White LED (3000K)</b>				
Lumen Output		1000 lm	1300 lm	1900 lm
LOR		0.78	0.78	0.78
CRI		80	80	80
Total Power		10.0W	13.8W	19.4W
Power Factor		0.90	0.94	0.94
Running Current		0.05A	0.06A	0.09A
Inrush Current		6A (20us)	4A (40us)	4A (40us)
Efficacy		78 lm/W	73 lm/W	76 lm/W
Emergency Output (BLF)		300 lm (30%)	273 lm (21%)	285 lm (15%)
<b>4 Neutral White LED (4000K)</b>				
Lumen Output		1100 lm	1400 lm	2000 lm
LOR		0.78	0.78	0.78
CRI		80	80	80
Total Power		10.0W	13.8W	19.4W
Power Factor		0.90	0.94	0.94
Running Current		0.05A	0.06A	0.09A
Inrush Current		6A (20us)	4A (40us)	4A (40us)
Efficacy		85 lm/W	79 lm/W	80 lm/W
Emergency Output (BLF)		330 lm (30%)	294 lm (21%)	300 lm (15%)

## Vici Pendant



### LED

8W	LED	PN455	LED	08	+	428
12W	LED	PN455	LED	12	+	428
17W	LED	PN455	LED	17	+	428

- Commercial quality pendant offering life expectancy of 50,000 hours (L80 B50)
- Available in a choice of lumen outputs, delivering up to 2000 lumens
- Efficacies up to 85 lm/W
- Colour stability within 3 MacAdams
- Creatively combines lightly etched borosilicate glass and spun steel housing in a choice of colours
- Wide choice of Gear Types available
- 2m Suspension supplied as standard (optional 5m available)

### Gear types F & G must be operated through a DSI


- A** Integral Driver
- E** Emergency
- F** Digital Dim
- G** Digital Dim + Emergency
- J** Switch Dim
- K** Switch Dim + Emergency
- S** DALI Dim
- T** DALI Dim + Emergency
- C** DALI Dim + DALI Emergency

3 Warm (3000K) 4 Neutral (4000K)

1 White (RAL 9010) 2 Urban Graphite (RAL 7046) 3 Black (RAL 9005)

330 5m Suspension (wire only)

### Photometrics



428 DLOR: 0.78