

Fig. M549 & 549E Cast Iron



FEATURES & BENEFITS


- Cast Iron with integral flanges
- Inside screw pattern with non-rising stem
- Ideal for use for non-corrosive and reasonably clean services
- Seat rings are threaded and securely fixed into the body



MATERIAL SPECIFICATION

Component	Material	Specification	
		BS EN	ASTM
Handwheel	Cast Iron	1561 EN-JLI030	A126 CI B
Gland	Cast Iron	1561 EN-JLI030	A126 CI B
Gland Packing	Expanded Graphite	-	-
Stuffing Box	Cast Iron	1561 EN-JLI030	A126 CI B
Stuffing Box Gasket	Asbestos Free	-	-
Stem	Brass	12164 CW614N	-
Bonnet	Cast Iron	1561 EN-JL1040	-
Bonnet Gasket	Asbestos Free	-	-
Wedge Nut	Brass	12164 CW614N	-
Wedge	Brass	12164 CW614N	-
Wedge Facing Ring	Bronze	1982 CC491K	-
Body Seat Ring	Bronze	1982 CC491K	-
Body	Cast Iron	1561 EN-JL1040	-

DIMENSIONAL DRAWING



DIMENSIONS & WEIGHTS

Nom Size	mm in	50 2	65 2 1/2	80 3	100 4	125 5	150 6	200 8	250 10	300 12
A PN6	mm	150	170	180	190	200	210	230	250	270
A Table E	in	5 3/4	6 1/4	6 1/2	6 3/4	7 1/2	8 1/4	9 1/2	10 3/4	12
B	mm	202	222	250	303	351	411	498	579	680
C	mm	130	130	150	185	185	195	225	245	185
D PN6	mm	140	160	190	210	240	265	320	375	440
D Table E	in	6	6 1/2	7 1/4	8 1/2	10	11	13 1/4	16	18
Weight	kg	13	16	22	29	40	51	88	150	205

PRESSURE/ TEMPERATURE RATING


BS EN 1171 PN6
6 bar at -10 to 120°C
5.4 bar at 150°C

TEST PRESSURES (HYDRAULIC)

Shell: 9 bar
Seat: 6.6 bar

SPECIFICATION

Inside screw.
Non-rising stem.
Bronze trim.
Flanged to BS EN 1092-2 PN6.
Also available flanged to BS10 Table E Fig. 549E.



Every effort has been made to ensure that the information contained in this publication is accurate at the time of publishing. Hattersley Ltd assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.