

LumiPanel - Large

Lumipanel 600 DB

3036755



Range features

- LumiPanel square dimensions:- Large: 600x600- Small: 300x300
- LumiPanel Round diameter:- XS: 121mm- Small: 172mm- Medium: 223mm- Large: 270mm
- Up to 3,300lm (600x600)
- For lay-in suspension, surface mounting and recessed mounting
- Square single colour driven with constant current: 600 at 1400mA and 300 at 500mA
- All RGB and Round versions driver at 24 DC



PRODUCT OVERVIEW

Ordering number	3036755
EAN code	8711971367550
Certifications	F-mark
Mount	Ceiling recessed
Housing	Aluminium
CRI (Ra)	85
Beam angle(°)	Wide
Colour temperature (K)	3000
Luminous flux (lm)	3302
Dimming range	10-100%
Voltage (V)	230
Lamps	160 High Brightness LEDs
Colour	Silver
IP rating	20

LumiPanel - Large

Lumipanel 600 DB

3036755

DATA TABLE

General data

Ordering number	3036755
EAN code	8711971367550
E-number SE	7099277
E-number FI	4270311
Certifications	F-mark
Mount	Ceiling recessed
Long description	LumiPanel square dimensions:- Large: 600x600- Small: 300x300. LumiPanel Round diameter:- XS: 121mm- Small: 172mm- Medium: 223mm- Large: 270mm . Up to 3,300lm (600x600). For lay-in suspension, surface mounting and recessed mounting. Square single colour driven with constant current: 600 at 1400mA and 300 at 500mA. All RGB and Round versions driver at 24 DC
Product name	Lumipanel 600 DB
Environment	Interior
General application	Culture, Health, Hotel, Office
Housing	Aluminium
Specific application	Offices
Sales pack quantity	1

Optical data

CRI (Ra)	85
Beam angle(°)	Wide
Colour temperature (K)	3000
Luminous flux (lm)	3302
Dimming range	10-100%
Distribution type	Direct - Symmetric
Glare control	UGR < 19

Electrical data

Total power consumption (W)	52
Voltage (V)	230
Drive current (mA)	1400mA
T Class min (°C)	-1
T Class max (°C)	-1
Electrical protection	Class III
Glow wire test	850°C
Lamps	160 High Brightness LEDs
Number of heads	1
Transformer availability	Not included
Transformer mounting	Remote

LumiPanel - Large

Lumipanel 600 DB

3036755

Physical data

Weight (kg)	6.75
Colour	Silver
Lamp included	No
IP rating	20
Cutout shape	Square
Recessed depth (mm)	25
Diffuser finish	Opal
Diffuser material	Polycarbonate
Emergency	Without
Single package dimensions (L x W x H) (cm)	72.00 x 65.60 x 6.60
Outer package dimensions (L x W x H) (cm)	77.00 x 69.00 x 31.00

LumiPanel - Large

Lumipanel 600 DB

3036755

PHOTOMETRY

