

LumiPanel - Small

Lumipanel 300 DB

3036759



Range features

- LumiPanel square dimensions:- Large: 600x600- Small: 300x300
- LumiPanel Round diameter:- XS: 121mm- Small: 172mm- Medium: 223mm- Large: 270mm
- Round 121mm, 172mm, 223mm and 270mm
- Up to 3300lm (600x600)
- For lay-in, suspension, wall mounting and recessed mounting
- Square single colour driven with constant current: 600 at 1400mA and 300 at 500mA
- All RGB and Round versions driver at 24 DC



PRODUCT OVERVIEW

Ordering number	3036759
EAN code	8711971367598
Certifications	F-mark
Mount	Ceiling recessed
Housing	Aluminium
CRI (Ra)	85
Beam angle(°)	Wide
Colour temperature (K)	3000
Luminous flux (lm)	1179
Dimming range	10-100%
Voltage (V)	230
Lamps	60 High Brightness LEDs
Colour	Silver
IP rating	20

LumiPanel - Small

Lumipanel 300 DB

3036759

DATA TABLE

General data

Ordering number	3036759
EAN code	8711971367598
E-number SE	7099280
Certifications	F-mark
Mount	Ceiling recessed
Long description	LumiPanel square dimensions:- Large: 600x600- Small: 300x300. LumiPanel Round diameter:- XS: 121mm- Small: 172mm- Medium: 223mm- Large: 270mm. Round 121mm, 172mm, 223mm and 270mm. Up to 3300lm (600x600). For lay-in, suspension, w all mounting and recessed mounting. Square single colour driven w ith constant current: 600 at 1400mA and 300 at 500mA. All RGB and Round versions driver at 24 DC
Product name	Lumipanel 300 DB
Environment	Interior
General application	Culture, Health, Hotel, Office
Housing	Aluminium
Specific application	Offices
Sales pack quantity	1

Optical data

CRI (Ra)	85
Beam angle(°)	Wide
Colour temperature (K)	3000
Luminous flux (lm)	1179
Dimming range	10-100%
Distribution type	Direct - Symmetric
Glare control	UGR < 19

Electrical data

Total power consumption (W)	19
Voltage (V)	230
Drive current (mA)	500mA
T Class min (°C)	-1
T Class max (°C)	-1
Electrical protection	Class III
Glow wire test	850°C
Lamps	60 High Brightness LEDs
Number of heads	1
Transformer availability	Not included
Transformer mounting	Remote

LumiPanel - Small

Lumipanel 300 DB

3036759

Physical data

Weight (kg)	1.88
Colour	Silver
Lamp included	No
IP rating	20
Cutout shape	Square
Recessed depth (mm)	25
Diffuser finish	Opal
Diffuser material	Polycarbonate
Emergency	Without
Single package dimensions (L x W x H) (cm)	38.70 x 33.60 x 6.00
Outer package dimensions (L x W x H) (cm)	40.20 x 35.20 x 26.50

LumiPanel - Small

Lumipanel 300 DB

3036759

PHOTOMETRY

