



A**Array**

Creative Range

ARRAY

Quality in every fibre

Specification

PRODUCT	Array Heavy Contract Tiles
FIBRE CONSTRUCTION	85% Polypropylene, 15% Polyamide
WEIGHT	4075gm metre ²
THICKNESS	9mm
TILE SIZE	 50cm x 50cm (Tiles are Bitumen backed)
COLOUR FASTNESS	Light (BS EN ISO 105:B02) >6 Wet Rubbing (BS EN ISO 105:B01) 4-5 Dry Rubbing (BS EN ISO 105:X12) 4-5
FLAMMABILITY	(BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char BS EN 13501:2002 Euroclass Bfl-s1
ANTISTATIC	Suitable for use in computer rooms
INSTALLATION	 Before laying Array tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels. Array tiles should be laid rotationally, alternating the direction of the tiles through 90°
ADHESIVE GUIDE	Use Tackifier F41 or Laybond 79. For details of subfloor preparation and a full guide to installation visit: www.heckmondwike-fb.co.uk
MAINTENANCE	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

EN 14041
Heckmondwike FB
Liversedge
WF15 7FH

12

Array Tile
Fibre Bonded Tile
Floorcovering
intended for
internal use

FM00644



Certificate No. EMS 73345



Manufactured in the UK

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may therefore show variations to the sample card. Heckmondwike FB reserves the right to change or modify product specifications without giving prior notice.


Heckmondwike
Quality in every fibre

Heckmondwike FB, A division of
National Floorcoverings Ltd.
Wellington Mills, Liversedge,
West Yorkshire WF15 7FH

Sales: 01924 406161 - Admin: 01924 410544

Free Fax: 0800 136769

sales@heckmondwike-fb.co.uk

www.heckmondwike-fb.co.uk