



NBS Specification – 2013 – Array Tile

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING

146 NEEDED PILE CARPET TILING:

As a UK manufacturer, Heckmondwike FB offers a wide range of heavy contract, fibre bonded carpet and tiles along with a range of specialist entrance area carpet and tiles. Each product range is available in a variety of colours and finishes providing durable, cost competitive products that are the perfect choice for areas of heavy wear and tear in the education sector, office environments, retail outlets, libraries, banks and similar.

Momentum

A range of 9mm thick bitumen backed 50 x 50 cm tiles manufactured with 85% polypropylene and 15% polyamide. Designed for use in Heavy contract areas, Array is available in 6 standard colourways.

Consult with Heckmondwike FB for technical literature and to obtain samples.

Preparation: This item can usually be deleted when the base is new and is mainly intended for existing surfaces. Consult Heckmondwike FB Installation Guide for recommendations and see clauses 460 to 520. Insert as appropriate.

Fabricated underlay: **Plywood as clause 560.** For use on timber floors only. Complete and include clause 560.

Carpet tiles: **Non woven**

Manufacturer: Heckmondwike FB A Division of National Floorcoverings Ltd, Wellington Mills, Liversedge, West Yorkshire WF15 7FH. Tel: 01924 406161, Fax: 0800 136769 Email: sales@heckmondwike-fb.co.uk Web: www.heckmondwike-fb.co.uk

Product reference: **Array Tile**

Type: **Rib carpet tile**

Size: **500 x 500 mm**

Colour/ pattern: **Lime/Magenta/Black/Blue/Red/Purple**

Method of laying: Consult Heckmondwike FB Installation Guide for recommendations and details. Heckmondwike FB recommend the use of Styccobond F41 adhesive for securing their carpet tiles- see F Ball & Co Ltd NBS PLUS page for details.