




B**Broadrib**





Fibre Bonded

BROADRIB

Quality in every fibre

Specification

PRODUCT	Broadrib Contract Heavy Carpet and Tiles
FIBRE CONSTRUCTION	80% Polypropylene, 20% Polyamide
WEIGHT	1020gm metre ² (Sheet), 4020gm metre ² (Tile)
THICKNESS	7.50mm (Sheet), 8.80mm (Tile)
ROLL WIDTH	 2 metre and 4 metre
TILE SIZE	 50cm x 50cm (Tiles are Bitumen backed)
COLOUR FASTNESS	Light (BS EN ISO 105:B02) >6 Wet Rubbing (BS EN ISO 105:B01) 5 Dry Rubbing (BS EN ISO 105:X12) 5
FLAMMABILITY	(BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot metal Nut test) - Low Radius of Char BS EN 13501:2002 Euroclass C _{fl} -s1 (Sheet) Euroclass C _{fl} -s1 (Tile)
REDUCTION IN IMPACT NOISE	BS EN ISO 140-8:20dB
ANTISTATIC	Suitable for use in computer rooms
INSTALLATION	 Before laying Broadrib tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels. Broadrib tiles should be laid rotationally, alternating the direction of the tiles through 90°
ADHESIVE GUIDE	Sheet carpet should be fully adhered with F Balls F3 or F52 or Laybond L47CV or 48X. Sheet carpets can be laid into F40 as a release system. For tiles use Tackifier F41 or Laybond 79. For details of subfloor preparation and a full guide to installation visit: www.heckmondwike-fb.co.uk
MAINTENANCE	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

<p>Sheet</p> <p>A+</p> <p>BREEAM Rating Certificate 363</p>	<p>Tile</p> <p>A</p> <p>BREEAM Rating Certificate 363</p>
<p>CE</p> <p>EN 14041</p> <p>Heckmondwike FB Liversedge WF15 7FH</p> <p>09</p> <p>Broadrib Sheet Fibre Bonded Sheet Floorcovering intended for internal use</p>	<p>CE</p> <p>EN 14041</p> <p>Heckmondwike FB Liversedge WF15 7FH</p> <p>09</p> <p>Broadrib Tile Fibre Bonded Sheet Floorcovering intended for internal use</p>
<p> C_{fl}-s1</p> <p> NPD</p>	<p> C_{fl}-s1</p> <p> NPD</p>



 **Manufactured in the UK**

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may therefore show variations to the sample card. Heckmondwike FB reserves the right to change or modify product specifications without giving prior notice.

 **Heckmondwike**
Quality in every fibre

Heckmondwike FB, A division of National Floorcoverings Ltd.
Wellington Mills, Liversedge, West Yorkshire WF15 7FH
Sales: 01924 406161 - Admin: 01924 410544
Free Fax: 0800 136769
sales@heckmondwike-fb.co.uk
www.heckmondwike-fb.co.uk