

D**Dreadnought**


Entrance Area

DREADNOUGHT

Quality in every fibre

Specification

PRODUCT	Dreadnought Heavy Contract Carpet and Tiles
FIBRE CONSTRUCTION	100% Polypropylene
WEIGHT	2437gm metre ² (Sheet), 4553gm metre ² (Tile)
THICKNESS	11mm (Sheet), 11.50mm (Tile)
ROLL WIDTH	 2 metre and 4 metre. Ribbing runs down length of roll
TILE SIZE	 50cm x 50cm (Tiles are Bitumen backed)
COLOUR FASTNESS	Light (BS EN ISO 105:B02) 6 Wet Rubbing (BS EN ISO 105:B01) 4-5 Dry Rubbing (BS EN ISO 105:X12) 4-5
FLAMMABILITY	(BS6307) Methanamine Pill Test - Pass

INSTALLATION	 Before laying Dreadnought tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels. Dreadnought tiles should be laid rotationally, alternating the direction of the tiles through 90°
--------------	--

ADHESIVE GUIDE	Sheet carpet should be fully adhered with F Balls F3 or Laybond L47CV. For tiles use Tackifier F41 or Laybond 79. For details of subfloor preparation and a full guide to installation visit: www.heckmondwike-fb.co.uk
----------------	--

MAINTENANCE	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk
-------------	---



 **Manufactured in the UK**

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may therefore show variations to the sample card. Heckmondwike FB reserves the right to change or modify product specifications without giving prior notice.

 **Heckmondwike**
Quality in every fibre

Heckmondwike FB, A division of
National Floorcoverings Ltd.
Wellington Mills, Liversedge,
West Yorkshire WF15 7FH

Sales: 01924 406161 - Admin: 01924 410544

Free Fax: 0800 136769

sales@heckmondwike-fb.co.uk

www.heckmondwike-fb.co.uk