



NBS Specification – 2013 – Montage Sheet

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING

186 NEEDED PILE CARPETING:

As a UK manufacturer, Heckmondwike FB offers a wide range of heavy contract, fibre bonded carpet and tiles along with a range of specialist entrance area carpet and tiles. Each product range is available in a variety of colours and finishes providing durable, cost competitive products that are the perfect choice for areas of heavy wear and tear in the education sector, office environments, retail outlets, libraries, banks and similar.

Montage

An 8.2mm thick sheet manufactured with 45% polypropylene, 30% Polyamide and 25% modacrylic. The sheet carpet is available in either 2.00mm or 4.00mm widths and is designed for use in areas such as corridors which suffer heavy traffic. The Montage carpet is suitable for other heavy contract areas.

Montage is available in 16 standard colourways.

Montage is also available in tile format - see M50/146 for details.

Consult with Heckmondwike FB for technical literature and to obtain samples.

Preparation: This item can usually be deleted when the base is new and is mainly intended for existing surfaces. Consult Heckmondwike FB Installation Guide for recommendations and see clauses 460 to 520. Insert as appropriate.

Fabricated underlay: **Plywood as clause 560.** For use on timber floors only. Complete and include clause 560.

Carpet underlay: **Not required.**

Carpet:

Manufacturer: Heckmondwike FB A Division of National Floorcoverings Ltd, Wellington Mills, Liversedge, West Yorkshire WF15 7FH. Tel: 01924 406161, Fax: 0800 136769 Email: sales@heckmondwike-fb.co.uk Web: www.heckmondwike-fb.co.uk

Product reference: Montage

Type: Heavy contract

Width: 4000 mm / 2000 mm.

Colour/ pattern: Ruby / Amethyst / Sapphire / Indigo / Magenta / Cobalt / Pacific Blue / Claret / Blueberry / Turquoise / Cerise / Bronzite / Flint / Topaz / Anthracite / Citrine

Carpet adhesive (and primer if recommended by manufacturer):

Consult Heckmondwike FB Installation Guide for recommendations and details.

Heckmondwike FB recommend the use of Styccobond F3 adhesive for fully adhering their carpets- Seams to be formed using a compression joint, with F30 seam sealer, see F Ball & Co Ltd NBS PLUS page for details.