




S**Supacord**







Fibre Bonded

SUPACORD

Quality in every fibre

Specification

PRODUCT	Supacord Heavy Contract Carpet and Tiles
FIBRE CONSTRUCTION	80% Polypropylene, 15% Polyamide, 5% Recycled Polyester
WEIGHT	1020gm metre ² (Sheet), 4020gm metre ² (Tile)
THICKNESS	6.20mm (Sheet), 7.60mm (Tile)
ROLL WIDTH	 2 metre and 4 metre. Ribbing runs down length of roll
TILE SIZE	 50cm x 50cm (Tiles are Bitumen backed)
COLOUR FASTNESS	Light (BS EN ISO 105:B02) 6 Wet Rubbing (BS EN ISO 105:B01) 4-5 Dry Rubbing (BS EN ISO 105:X12) 4-5
FLAMMABILITY	(BS5287) Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char BS EN 13501:2002 Euroclass C _{fl} -s1 (Sheet) Euroclass B _{fl} -s1 (Tile)
REDUCTION IN IMPACT NOISE	BS EN ISO 140-8:19dB
ANTISTATIC	Suitable for use in computer rooms
INSTALLATION	 The method of installation should conform to BS5325. For details of subfloor preparation and a full guide to installation visit: www.heckmondwike-fb.co.uk Before laying Supacord tiles should be allowed to condition for 24 hours at the expected temperature and humidity levels. Supacord tiles should be laid rotationally, alternating the direction of the tiles through 90°
ADHESIVE GUIDE	Sheet carpet should be fully adhered with F Balls F3 or F52 or Laybond L47CV. Sheet carpets can be laid into F40 as a release system. For tiles use Tackifier F41 or Laybond 79.
MAINTENANCE	To achieve maximum life expectancy it is essential to initiate a maintenance schedule from the date of installation. A full guide to cleaning & maintenance is available at: www.heckmondwike-fb.co.uk

Sheet	Tile
A+ BREEAM Rating Certificate 363	A+ BREEAM Rating Certificate 363
 EN 14041 Heckmondwike FB Liversedge WF15 7FH 09 Supacord Sheet Fibre Bonded Sheet Floorcovering intended for internal use	 EN 14041 Heckmondwike FB Liversedge WF15 7FH 09 Supacord Tile Fibre Bonded Tile Floor- covering intended for internal use
 C _{fl} -s1	 B _{fl} -s1
 NPD	 NPD



Heckmondwike
Quality in every fibre

Heckmondwike FB, A division of
National Floorcoverings Ltd.
Wellington Mills, Liversedge,
West Yorkshire WF15 7FH

Sales: 01924 406161 - Admin: 01924 410544

Free Fax: 0800 136769

sales@heckmondwike-fb.co.uk

www.heckmondwike-fb.co.uk



BESA



Manufactured in the UK

PLEASE NOTE: For technical reasons, as with all textile materials, it is not possible to colour match from different batches. Orders that need to colour match should be placed at the same time. Production may therefore show variations to the sample card. Fibre compositions of colours within ranges may vary. Heckmondwike FB reserves the right to change or modify product specifications without giving prior notice.