


Heavy Contract Carpet and Tiles




Heckmondwike
Quality in every fibre




Graphite




Flint




Claret




Seal




Lavender



Anthracite



Red




Mulberry



Kingston Grey




Moorland




Orange




Amethyst




Blueberry



Azure



Indigo



Cobalt




Violet



Pacific Blue




Kingfisher




Damson




Astra Blue



Moonlight



Acorn




Gunmetal




Safari




Pale Olive




Arctic Blue




Pebble




Green



Emerald



Opal



Willow


Heckmondwike Supacord

Fibre Bonded


Popular Supacord is widely specified for many education buildings across the UK. In addition to the education sector, Supacord can be found in retail outlets, office environments and public sector buildings. Supacord is highly cost competitive and is the perfect choice for areas of heavy wear and tear.




Steel Grey



Magenta




Heather



Purple



Blue




Blue Moon




Onyx





Sherwood



Aquamarine



Yellow

Specification	Supacord	
Fibre Construction (Sheet)	80% Polypropylene, 20% Polyamide	
Fibre Construction (Tile)	80% Polypropylene, 20% Polyamide	
Colour Fastness	Light (BS EN ISO 105:B02) 6 Wet Rubbing (BS EN ISO 105:B01) 4-5 Dry Rubbing (BS EN ISO 105:X12) 4-5	
Flammability	BS5287 Assessment and labelling of Textile Floorcoverings tested to BS4790 (Hot Metal Nut Test) - Low Radius of Char BS EN 13501:2002 Euroclass C _{ff} -s1 (Sheet) Euroclass B _{ff} -s1 (Tile)	
Antistatic	Suitable for use in computer rooms	
Formats	Sheet 	Tiles 
Backing	-	Bitumen
Size	2 metre and 4 metre. Ribbing runs down length of roll	50cm x 50cm
Weight	1020gm metre ²	4020gm metre ²
Thickness	6.20mm	7.60mm
BREEAM Rating	A+ (Certificate 363 for office, schools & retail)	A (Certificate 363 for office, schools & retail)



BESA



Manufactured in the UK

E & OE

Heckmondwike FB reserves the right to change or modify product specifications without giving prior notice. Colours are limited to the print process and may differ slightly to the actual product.

05/2012

 **Heckmondwike**
Quality in every fibre

Heckmondwike FB, A division of
National Floorcoverings Ltd.
Wellington Mills, Liversedge,
West Yorkshire WF15 7FH

Sales: 01924 406161 - Admin: 01924 410544

Free Fax: 0800 136769

sales@heckmondwike-fb.co.uk

www.heckmondwike-fb.co.uk