

# MINI CORNICHE

## Applique

IP65  
IK 05

available colors:  
■ .06 grey



Body made of extruded, painted, corrosion resistant, aluminium alloy. A4 stainless steel screws. AISI 316 stainless steel mounting brackets. 5mm thick extra-clear flat tempered glass cover. Protection with anodizing treatment, epoxy powder base coating and polyester painting. External power supply by 24V DC/700mA transformer. Product supplied with 2m power cable. Gore valve to prevent condensation inside the product.

Corps en aluminium extrudé résistant à la corrosion. Vis en acier inox A4. Étriers de fixation en acier inox AISI 316. Diffuseur en verre trempé plat extra clair de 5mm d'épaisseur. Protection de l'ensemble par traitement d'anodisation, avec primaire époxy et peinture polyester. Alimentation déportée, courant continu de 24 V DC ou 700mA. Appareil livré avec 2m de câble. Valve en Gore évitant la formation de condensation à l'intérieur du produit.



MONTAGNE ST. EMILION  
FRANCE



- 1 Gore valve to prevent condensation inside the product.
- 2 Wall fixing bracket available as accessory code 8947005
- 3 Wall fixing bracket available as accessory code 8947010
- 4  $\pm 45^\circ$  adjustable standard brackets
- 5 Extra-clear glass (for maximum light transmission)
- 6 Product supplied with 2 m cable

- 1 Valve en Gore évitant la formation de condensation à l'intérieur du produit.
- 2 Étrier court pour fixation murale du produit code 8947005
- 3 Étrier long pour fixation murale du produit code 8947010
- 4 Étriers standard orientables  $\pm 45^\circ$
- 5 Verre extra-clair (transmission maximale de la lumière)
- 6 Appareil livré avec 2m de câble



3 LED  
24V DC  
100 mm

POWER SUPPLY TO BE ORDERED SEPARATELY





**84 11 1X1**  
3W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 1X3**  
3W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 1X8**  
3W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



**84 11 1X7**  
3W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



How to create the product code?

WHITE versions available:  
1 = 3000K (375 lm)  
6 = 4000K (420 lm)

Other versions available  
ON REQUEST:  
9 = 2700K (375 lm)  
7 = 5000K (420 lm)  
4 = Amber  
2 = Red  
3 = Green  
5 = Blue

3 LED Dynamic  
max. 700mA  
100 mm

POWER SUPPLY TO BE ORDERED SEPARATELY



**84 91 1X1**  
7W LED  
max. 700mA  
3 channels  
power supply excluded  
Class III

A A+ A++

**84 91 1X3**  
7W LED  
max. 700mA  
3 channels  
power supply excluded  
Class III

A A+ A++

**84 91 1X8**  
7W LED  
max. 700mA  
3 channels  
power supply excluded  
Class III

A A+ A++

**84 91 1X7**  
7W LED  
max. 700mA  
3 channels  
power supply excluded  
Class III

A A+ A++

How to create the product code?


Dynamic versions available:  
0 = RGB

other versions available  
ON REQUEST  
8 = Dynamic White

Control systems for dynamic light p. 374

Systèmes de contrôle pour lumière dynamique p. 374

Technical data



ACCESSORIES

- 89 17 006**  
Connector Micro Paguro IP68  
max. 2 x 0.75 mm<sup>2</sup> Ø 4.8 - 6 mm  
Connecteur Micro Gel IP68  
max. 2 x 0.75mm<sup>2</sup> Ø 4,8 - 6mm
- 89 47 005**  
Stainless steel brackets for wall mounting length 5cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 5 cm (orientable ±90°)

- 89 17 007**  
Mini Quick Connector IP68  
3 x 1.5 mm<sup>2</sup> Ø 7 - 12 mm  
Mini Connecteur Rapide IP68  
3 x 1,5mm<sup>2</sup> Ø 7 - 12mm
- 89 47 010**  
Stainless steel brackets for wall mounting length 10cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 10 cm (orientable ±90°)

- 89 17 004**  
Connector Paguro IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9.5 - 12 mm  
Connecteur Gel IP68  
max. 3 x 4mm<sup>2</sup> Ø 9,5 - 12mm
- 89 47 015**  
Stainless steel brackets for lateral mounting  
Étrier en acier inox pour fixation latérale

ACCESSORIES 24V DC

- 89 56 072**  
Power supply unit IP67 24V DC 70W  
Alimentation IP67 24V DC 70W
- 89 56 074**  
Power supply unit IP67 24V DC 150W  
Alimentation IP67 24V DC 150W

- 89 56 073**  
Power supply unit IP20 24V DC 100W  
Alimentation IP20 24V DC 100W
- 89 56 075**  
Power supply unit IP20 24V DC 200W  
Alimentation IP20 24V DC 200W

- 89 56 108**  
Power supply unit IP20 24V DC 150W  
Alimentation IP20 24V DC 150W
- 89 56 076**  
Power supply unit IP20 24V DC 480W  
Alimentation IP20 24V DC 480W





9 LED  
24V DC  
300 mm

POWER SUPPLY TO BE ORDERED SEPARATELY





**84 11 3X1**  
9W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 3X3**  
9W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 3X8**  
9W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



**84 11 3X7**  
9W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



How to create the product code?

WHITE versions available:  
1 = 3000K (1125 lm)  
6 = 4000K (1260 lm)

Other versions available  
ON REQUEST:  
9 = 2700K (1125 lm)  
7 = 5000K (1260 lm)  
4 = Amber  
2 = Red  
3 = Green  
5 = Blue

9 LED Dynamic  
max. 700mA  
300 mm

POWER SUPPLY TO BE ORDERED SEPARATELY

**84 91 3X1**  
20,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 3X3**  
20,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 3X8**  
20,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 3X7**  
20,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

How to create the product code?


Dynamic versions available:  
0 = RGB

other versions available  
ON REQUEST  
8 = Dynamic White

Control systems for dynamic light p. 374

Systèmes de contrôle pour lumière dynamique p. 374

Technical data



ACCESSORIES

**89 17 006**  
Connector Micro Paguro IP68  
max. 2 x 0,75 mm<sup>2</sup> Ø 4,8 - 6 mm  
Connecteur Micro Gel IP68  
max. 2 x 0,75 mm<sup>2</sup> Ø 4,8 - 6 mm

**89 47 005**  
Stainless steel brackets for wall mounting length 5cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 5 cm (orientable ±90°)

**89 17 007**  
Mini Quick Connector IP68  
3 x 1,5 mm<sup>2</sup> Ø 7 - 12 mm  
Mini Connecteur Rapide IP68  
3 x 1,5 mm<sup>2</sup> Ø 7 - 12 mm

**89 47 010**  
Stainless steel brackets for wall mounting length 10cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 10 cm (orientable ±90°)

**89 17 004**  
Connector Paguro IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9,5 - 12 mm  
Connecteur Gel IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9,5 - 12 mm

**89 47 015**  
Stainless steel brackets for lateral mounting  
Étriers en acier inox pour fixation latérale

ACCESSORIES 24V DC

**89 56 072**  
Power supply unit IP67 24V DC 70W  
Alimentation IP67 24V DC 70W

**89 56 073**  
Power supply unit IP20 24V DC 100W  
Alimentation IP20 24V DC 100W

**89 56 108**  
Power supply unit IP20 24V DC 150W  
Alimentation IP20 24V DC 150W

**89 56 074**  
Power supply unit IP67 24V DC 150W  
Alimentation IP67 24V DC 150W

**89 56 075**  
Power supply unit IP20 24V DC 200W  
Alimentation IP20 24V DC 200W

**89 56 076**  
Power supply unit IP20 24V DC 480W  
Alimentation IP20 24V DC 480W



PONT DE LA MATTE  
NANTES, FRANCE





18 LED  
24V DC  
600 mm

POWER SUPPLY TO BE ORDERED SEPARATELY



**84 11 5X1**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 5X3**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 5X8**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



**84 11 5X7**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



How to create the product code?

WHITE versions available:  
1 = 3000K (2250 lm)  
6 = 4000K (2520 lm)  
Other versions available  
ON REQUEST:  
9 = 2700K (2250 lm)  
7 = 5000K (2520 lm)  
4 = Amber  
2 = Red  
3 = Green  
5 = Blue

18 LED Dynamic  
max. 700mA  
600 mm

POWER SUPPLY TO BE ORDERED SEPARATELY

**84 91 5X1**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 5X3**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 5X8**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 5X7**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III


A A+ A++

How to create the product code?

Dynamic versions available:  
0 = RGB  
Other versions available  
ON REQUEST  
8 = Dynamic White

Control systems for dynamic light p. 374  
Systèmes de contrôle pour lumière dynamique p. 374

Technical data



ACCESSORIES

- 89 17 006**  
Connector Micro Paguro IP68  
max. 2 x 0,75 mm<sup>2</sup> Ø 4,8 - 6 mm  
Connecteur Micro Gel IP68  
max. 2 x 0,75 mm<sup>2</sup> Ø 4,8 - 6 mm
- 89 47 005**  
Stainless steel brackets for wall mounting length 5cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 5 cm (orientable ±90°)

- 89 17 007**  
Mini Quick Connector IP68  
3 x 1,5 mm<sup>2</sup> Ø 7 - 12 mm  
Mini Connecteur Rapide IP68  
3 x 1,5 mm<sup>2</sup> Ø 7 - 12 mm
- 89 47 010**  
Stainless steel brackets for wall mounting length 10cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 10 cm (orientable ±90°)

- 89 17 004**  
Connector Paguro IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9,5 - 12 mm  
Connecteur Gel IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9,5 - 12 mm
- 89 47 015**  
Stainless steel brackets for lateral mounting  
Étriers en acier inox pour fixation latérale

ACCESSORIES 24V DC

- 89 56 072**  
Power supply unit IP67 24V DC 70W  
Alimentation IP67 24V DC 70W
- 89 56 074**  
Power supply unit IP67 24V DC 150W  
Alimentation IP67 24V DC 150W

- 89 56 073**  
Power supply unit IP20 24V DC 100W  
Alimentation IP20 24V DC 100W
- 89 56 075**  
Power supply unit IP20 24V DC 200W  
Alimentation IP20 24V DC 200W

- 89 56 108**  
Power supply unit IP20 24V DC 150W  
Alimentation IP20 24V DC 150W
- 89 56 076**  
Power supply unit IP20 24V DC 480W  
Alimentation IP20 24V DC 480W





18 LED  
24V DC  
900 mm

POWER SUPPLY TO BE ORDERED SEPARATELY



**84 11 4X1**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 4X3**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 4X8**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



**84 11 4X7**  
18W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



How to create the product code?

WHITE versions available:  
1 = 3000K (2250 lm)  
6 = 4000K (2520 lm)  
  
Other versions available  
ON REQUEST:  
9 = 2700K (2250 lm)  
7 = 5000K (2520 lm)  
4 = Amber  
2 = Red  
3 = Green  
5 = Blue

18 LED Dynamic  
max. 700mA  
900 mm

POWER SUPPLY TO BE ORDERED SEPARATELY

**84 91 4X1**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 4X3**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 4X8**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 4X7**  
40,5W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III


A A+ A++

How to create the product code?

Dynamic versions available:  
0 = RGB  
  
Other versions available  
ON REQUEST  
8 = Dynamic White

Control systems for dynamic light p. 374  
Systèmes de contrôle pour lumière dynamique p. 374

Technical data



ACCESSORIES

- 89 17 006**  
Connector Micro Paguro IP68  
max. 2 x 0,75 mm<sup>2</sup> Ø 4,8 - 6 mm  
Connecteur Micro Gel IP68  
max. 2 x 0,75mm<sup>2</sup> Ø 4,8 - 6mm
- 89 47 005**  
Stainless steel brackets for wall mounting length 5cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 5 cm (orientable ±90°)

- 89 17 007**  
Mini Quick Connector IP68  
3 x 1,5 mm<sup>2</sup> Ø 7 - 12 mm  
Mini Connecteur Rapide IP68  
3 x 1,5mm<sup>2</sup> Ø 7 - 12mm
- 89 47 010**  
Stainless steel brackets for wall mounting length 10cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 10 cm (orientable ±90°)

- 89 17 004**  
Connector Paguro IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9,5 - 12 mm  
Connecteur Gel IP68  
max. 3 x 4mm<sup>2</sup> Ø 9,5 - 12mm
- 89 47 015**  
Stainless steel brackets for lateral mounting  
Étriers en acier inox pour fixation latérale

ACCESSORIES 24V DC

- 89 56 072**  
Power supply unit IP67 24V DC 70W  
Alimentation IP67 24V DC 70W
- 89 56 074**  
Power supply unit IP67 24V DC 150W  
Alimentation IP67 24V DC 150W

- 89 56 073**  
Power supply unit IP20 24V DC 100W  
Alimentation IP20 24V DC 100W
- 89 56 075**  
Power supply unit IP20 24V DC 200W  
Alimentation IP20 24V DC 200W

- 89 56 108**  
Power supply unit IP20 24V DC 150W  
Alimentation IP20 24V DC 150W
- 89 56 076**  
Power supply unit IP20 24V DC 480W  
Alimentation IP20 24V DC 480W



27 LED  
24V DC  
900 mm

POWER SUPPLY TO BE ORDERED SEPARATELY





**84 11 7X1**  
27W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 7X3**  
27W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 7X8**  
27W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



**84 11 7X7**  
27W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



How to create the product code?

WHITE versions available:  
1 = 3000K (3375 lm)  
6 = 4000K (3780 lm)

Other versions available  
ON REQUEST:  
9 = 2700K (3375 lm)  
7 = 5000K (3780 lm)  
4 = Amber  
2 = Red  
3 = Green  
5 = Blue

27 LED Dynamic  
max. 700mA  
900 mm

POWER SUPPLY TO BE ORDERED SEPARATELY

**84 91 7X1**  
61W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 7X3**  
61W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 7X8**  
61W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 7X7**  
61W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++


How to create the product code?

Dynamic versions available:  
0 = RGB

other versions available  
ON REQUEST  
8 = Dynamic White

Control systems for dynamic light p. 374  
Systèmes de contrôle pour lumière dynamique p. 374

Technical data



ACCESSORIES

- 89 17 006**  
Connector Micro Paguro IP68  
max. 2 x 0,75 mm<sup>2</sup> Ø 4,8 - 6 mm  
Connecteur Micro Gel IP68  
max. 2 x 0,75mm<sup>2</sup> Ø 4,8 - 6mm
- 89 47 005**  
Stainless steel brackets for wall mounting length 5cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 5 cm (orientable ±90°)

- 89 17 007**  
Mini Quick Connector IP68  
3 x 1,5 mm<sup>2</sup> Ø 7 - 12 mm  
Mini Connecteur Rapide IP68  
3 x 1,5mm<sup>2</sup> Ø 7 - 12mm
- 89 47 010**  
Stainless steel brackets for wall mounting length 10cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 10 cm (orientable ±90°)

- 89 17 004**  
Connector Paguro IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9,5 - 12 mm  
Connecteur Gel IP68  
max. 3 x 4mm<sup>2</sup> Ø 9,5 - 12mm
- 89 47 015**  
Stainless steel brackets for lateral mounting  
Étriers en acier inox pour fixation latérale

ACCESSORIES 24V DC

- 89 56 072**  
Power supply unit IP67 24V DC 70W  
Alimentation IP67 24V DC 70W

- 89 56 073**  
Power supply unit IP20 24V DC 100W  
Alimentation IP20 24V DC 100W

- 89 56 108**  
Power supply unit IP20 24V DC 150W  
Alimentation IP20 24V DC 150W

- 89 56 074**  
Power supply unit IP67 24V DC 150W  
Alimentation IP67 24V DC 150W

- 89 56 075**  
Power supply unit IP20 24V DC 200W  
Alimentation IP20 24V DC 200W

- 89 56 076**  
Power supply unit IP20 24V DC 480W  
Alimentation IP20 24V DC 480W







36 LED  
24V DC  
1200 mm

POWER SUPPLY TO BE ORDERED SEPARATELY



**84 11 6X1**  
36W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 6X3**  
36W LED  
24V DC  
power supply excluded  
Class III

A A+ A++





**84 11 6X8**  
36W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



**84 11 6X7**  
36W LED  
24V DC  
power supply excluded  
Class III

A A+ A++



How to create the product code?

WHITE versions available:  
1 = 3000K (4500 lm)  
6 = 4000K (5040 lm)

Other versions available  
ON REQUEST:  
9 = 2700K (4500 lm)  
7 = 5000K (5040 lm)  
4 = Amber  
2 = Red  
3 = Green  
5 = Blue

36 LED Dynamic  
max. 700mA  
1200 mm

POWER SUPPLY TO BE ORDERED SEPARATELY

**84 91 6X1**  
81W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 6X3**  
81W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 6X8**  
81W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

**84 91 6X7**  
81W LED  
max. 700mA  
3 channels + 1 channel NTC  
power supply excluded  
Class III

A A+ A++

How to create the product code?


Dynamic versions available:  
0 = RGB

other versions available  
ON REQUEST  
8 = Dynamic White

Control systems for dynamic light p. 374

Systèmes de contrôle pour lumière dynamique p. 374

Technical data



ACCESSORIES

- 89 17 006**  
Connector Micro Paguro IP68  
max. 2 x 0,75 mm<sup>2</sup> Ø 4,8 - 6 mm  
Connecteur Micro Gel IP68  
max. 2 x 0,75mm<sup>2</sup> Ø 4,8 - 6mm
- 89 47 005**  
Stainless steel brackets for wall mounting length 5cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 5 cm (orientable ±90°)

- 89 17 007**  
Mini Quick Connector IP68  
3 x 1,5 mm<sup>2</sup> Ø 7 - 12 mm  
Mini Connecteur Rapide IP68  
3 x 1,5mm<sup>2</sup> Ø 7 - 12mm
- 89 47 010**  
Stainless steel brackets for wall mounting length 10cm (±90° adjustable)  
Étrier en acier inox pour fixation murale longueur 10 cm (orientable ±90°)

- 89 17 004**  
Connector Paguro IP68  
max. 3 x 4 mm<sup>2</sup> Ø 9,5 - 12 mm  
Connecteur Gel IP68  
max. 3 x 4mm<sup>2</sup> Ø 9,5 - 12mm
- 89 47 015**  
Stainless steel brackets for lateral mounting  
Étriers en acier inox pour fixation latérale

ACCESSORIES 24V DC

- 89 56 072**  
Power supply unit IP67 24V DC 70W  
Alimentation IP67 24V DC 70W
- 89 56 074**  
Power supply unit IP67 24V DC 150W  
Alimentation IP67 24V DC 150W

- 89 56 073**  
Power supply unit IP20 24V DC 100W  
Alimentation IP20 24V DC 100W
- 89 56 075**  
Power supply unit IP20 24V DC 200W  
Alimentation IP20 24V DC 200W

- 89 56 108**  
Power supply unit IP20 24V DC 150W  
Alimentation IP20 24V DC 150W
- 89 56 076**  
Power supply unit IP20 24V DC 480W  
Alimentation IP20 24V DC 480W