

PIX

Bulkhead - Applique Plafonnier - Applique

230V
IP65
IK 07

available colors:

- .02 white
- .06 grey
- .08 antrachite




Body and fixing plate made of die-cast aluminium alloy, corrosion resistant. Protection with anodizing treatment, epoxy powder base coating and polyester painting. 4mm thick white flat tempered glass. Product with no visible screws and completely hidden fixing plate. Double cable input \varnothing 7-13 mm.

Corps et base en aluminium moulé sous pression, résistant à la corrosion. Protection de l'ensemble par traitement d'anodisation avec primaire époxy et peinture polyester. Diffuseur en verre trempé plat extra clair ou sablé de 5mm d'épaisseur. Sans vis apparentes platine de fixation murale totalement invisible. Double entrée de câble \varnothing 7-13mm.




**PIX 40
LED
230V**



diffuse

POWER SUPPLY INCLUDED




50 40 3X6
16W / 23W LED
220-240V 0/50/60Hz
power supply included
Class I


**SETTING POWER SUPPLY
INCLUDED**

**MOD OFF = 16W (default setting)
MOD ON = 23W**


A A+ A++



downlight



applique



**PIX 40
LED
230V 1-10V**

POWER SUPPLY DIMMABLE INCLUDED




50 40 4X6
16W / 23W LED
220-240V 0/50/60Hz
Dimmable 1-10V
power supply included
Class I


**SETTING POWER SUPPLY
INCLUDED**

**MOD OFF = 16W (default setting)
MOD ON = 23W**


A A+ A++



downlight



applique



How to create the product code?

WHITE versions available:
1 = 16W 3000K (1862 lm)
6 = 16W 4000K (2234 lm)

WHITE versions available:
1 = 23W 3000K (2020 lm)
6 = 23W 4000K (2425 lm)

**SETTING POWER SUPPLY
INCLUDED**

**MOD OFF = 16W (default setting)
MOD ON = 23W**

How to create the product code?


WHITE versions available:
1 = 16W 3000K (1862 lm)
6 = 16W 4000K (2234 lm)

WHITE versions available:
1 = 23W 3000K (2020 lm)
6 = 23W 4000K (2425 lm)

**SETTING POWER SUPPLY
INCLUDED**


**MOD OFF = 16W (default setting)
MOD ON = 23W**

Technical data





PIX 26
LED
230V




diffuse

POWER SUPPLY INCLUDED




50 26 3X6
7,5W LED
220-240V 0/50/60Hz
power supply included
Class I



A A+ A++



downlight



applique



diffuse


PIX 26
LED
230V

POWER SUPPLY INCLUDED




50 26 4X6
11W LED
220-240V 0/50/60Hz
power supply included
Class I


A A+ A++



downlight



applique



How to create the product code?

WHITE versions available:
1 = 3000K (730 lm)
6 = 4000K (875 lm)

How to create the product code?

WHITE versions available:
1 = 3000K (875 lm)
6 = 4000K (1050 lm)

Technical data

