

Product/DoP Ref: 025CPR13

Product-type: BOX 75

Product intended to be used in walls and partitions

Manufacturer	Notified Body
IG (Lintels) Ltd., Avondale Road, Cwmbran, Gwent, NP44 1XY	Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type <i>BOX 75</i> is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2013.	Ceram No. 1289, conducted determination of the product –type. The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2013. The AVCP for the product is system 3.

Essential characteristics	Lintel length (mm)		hEN
	0600-1650	1800	
Load Bearing Capacity (kN) - <i>Total UDL</i>	Figures shown are safe working loads 15	10	EN 845-2: 2013
Deflection Under Load	Less than Effective Span/325 at maximum safe working load		
Mass Per Unit Area	NPD		
Water Absorption	Zero		
Thermal Resistance (W/mK)	50		
Resistance to Fire	NPD (Contact IG Technical Department for information)		
Durability (against corrosion)	L16.1		
Durability (against freeze/thaw)	Resistant		
Dangerous Substances	None		

Date: 04/03/2015

Issued under the sole responsibility of IG Lintels, signed by



Sean Coyle (CEO)