

Product/DoP Ref: 021CPR13

Product-type: L7 100

*Product intended to be used in walls and partitions*

Manufacturer	Notified Body
IG (Lintels) Ltd., Avondale Road, Cwmbran, Gwent, NP44 1XY	Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type <i>L7 100</i> is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2013.	Ceram No. 1289, conducted determination of the product –type.  The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2013. The AVCP for the product is system 3.

Essential characteristics		Lintel length (mm)					hEN
		0600-1200	1350-1800	1950-2400	2550-3600	3750-4500	
Load Bearing Capacity (kN) - Total UDL	<b>Figures shown are safe working loads</b>	4	5	5	9	12	EN 845-2: 2013
Deflection Under Load		Less than Effective Span/325 at maximum safe working load					
Mass Per Unit Area		NPD					
Water Absorption		Zero					
Thermal Resistance (W/mK)		50					
Resistance to Fire		NPD (Contact IG Technical Department for information)					
Durability (against corrosion)		L14					
Durability (against freeze/thaw)		Resistant					
Dangerous Substances		None					

**Date:** 04/03/2015

**Issued under the sole responsibility of IG Lintels, signed by**



Sean Coyle (CEO)