

Product/DoP Ref: 022CPR13

Product-type: L7/HD 50


Product intended to be used in walls and partitions

Manufacturer	Notified Body
IG (Lintels) Ltd., Avondale Road, Cwmbran, Gwent, NP44 1XY	Ceram, Queens Road, Penkhull, Stoke-on-Trent, Staffordshire, ST4 7LQ
IG Lintels, in accordance with the Construction Products Regulation (EU) No. 305/2011, hereby declares that product type <i>L7/HD 50</i> is manufactured to the requirements of the Harmonised European Standard EN 845-2: 2013.	Ceram No. 1289, conducted determination of the product –type. The conformity of the product was determined as per the requirements stipulated in ZA.2 and ZA.3 of EN 845-2: 2013. The AVCP for the product is system 3.

Essential characteristics		Lintel length (mm)			hEN
		0600-1650	1800-2400	2550-3000	
Load Bearing Capacity (kN) - Total UDL	<i>Figures shown are safe working loads</i>	10	12	12	EN 845-2: 2013
Deflection Under Load		Less than Effective Span/325 at maximum safe working load			
Mass Per Unit Area		NPD			
Water Absorption		Zero			
Thermal Resistance (W/mK)		50			
Resistance to Fire		NPD (Contact IG Technical Department for information)			
Durability (against corrosion)		L14			
Durability (against freeze/thaw)		Resistant			
Dangerous Substances		None			

Date: 04/03/2015

Issued under the sole responsibility of IG Lintels, signed by

 Sean Coyle (CEO)