

GENERAL INFORMATION:

- The sheet material should be stored flat and protected from damage for a period of 24 hours at ambient temperature before use.
- The sheet achieves Class "0" fire rating. If the sheet is to be used where there is a likelihood of extremes in changes of temperature, please contact our technical representative.
- If using adhesive to fix this product rather than double sided tape, please refer to current C.O.S.H.H. information and data sheets which are provided with the product (copies available on request).
- The sheet may be cut to size and shaped at works or on site, using a fine toothed saw or sharp "Stanley" knife. All sharp edges should be removed by means of fine file or suitable abrasive sheet.

ADHESIVE INSTALLATION PROCEDURE:

1. Shake the can thoroughly before use, hold the can 25cm away from the surface and commence to spray.
2. A Two Way Wet Stick is required, apply adhesive to both the reverse side of the sheet and to the substrate, leave the adhesive to go tacky for 2-3 minutes.
3. Fit the sheet in position.
4. Consolidate by applying heavy pressure over the entire surface by means of a heavy roller or clamping.
5. Allow 24 hours for adhesive to set
6. **IMPORTANT NOTE:** Please ensure that the surface is dry and clean from dirt, dust & grease before attempting to bond.

Note:

Refer to adhesive Data Sheet for C.O.S.H.H.

requirements, these are supplied upon request.

FIXING INSTRUCTION

In case of technical queries please contact: Intastop Ltd, Holly House, Kelham St. Ind.
Est, Doncaster, South Yorkshire DN1 3QZ
Tel :01302 364666 Fax: 01302 364777
E-mail: technical@intastop.com
Internet: www.intastop.com