



Interface® | Barricade

SPECIFICATION

Product definition	Tufted Patterned Textured Cut Tile	Style number	60573
Pile Material	100% Nylon	Wear Classification	EN 1307:32 Contract General
Pile Yarn Weight	750 ± 10%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
Effective pile yarn weight	565 ± 10%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Total Weight	4479 ± 7.5 %	Castor Chair Rating	≥ 2,0 (EN 985)
Pile Height	4.0 ± 0.4 mm	Dimensional Stability	≤ 0,2% (ISO 2551 / EN 986)
Total Thickness	7.9 ± 0.4 mm	Vertical Electrical Resistance	
Gauge/Ends per 10cm	1/8 - 36	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Tufts per m2	118,800 ± 7.5%	Tiles per Box	16 - 4 m² (50 x 50 cm ± 0,2%)
Backing Type	Graphlex®		



www.interface.com



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

Interface Europe Ltd reserve the right to change or modify specifications