

Interface® | Biosfera I Boucle

SPECIFICATION

Product definition	Tufted Level Loop Pile	Style number	60718
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	530g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501)
Effective pile yarn weight	340g/m ² ± 10%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Total Weight	4190g/m ² ± 5%	Castor Chair Rating	≥ 2,4 (EN 985)
Pile Height	2.4 ± 0.3 mm	Dimensional Stability	≤ 0,2% (ISO 2551 / EN 986)
Total Thickness	5,6 mm ± 0,3 mm	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965)
Gauge/Ends per 10cm	1/10 - 39.4	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Tufts per m2	164,000 ± 7,5%	Tiles per Box	20 - 5 (50 x 50 cm ± 0,2%)
Backing Type	Graphlex®		

CE
0336-CPD-8538
EN 14041:2004

Cfl-s1

BS

≤10⁹Ω

EN 1307

Monolithic

GUT

24976

25 dB



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications