

Interface® | Chenille Warp

SPECIFICATION

Product definition	Tufted Patterned Level Tip Sheared Tile	Style number	3462900405
Pile Material	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	568g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Bfl S1 (EN ISO 13501) (NFP 92-506) (PV No. 95.40716) M3
Total Weight	4319g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	3.0 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	6.5 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)
Gauge/Ends per 10cm	1/12 - 47.2	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Tufts per m²	167,560 ± 5%	Colour Fastness - Light	6 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4 m ² (50 x 50 cm ± 0.15%)

CE
06
0336-CPD-8538
Bfl-s1
BS
EN 1307

Quarter Turn Ashlar Brick
GuT 8D7B9D7F 25dB EMS 32802 FM 00679
ISO 14001 ISO 9001 ISO 45001
Incremental Pilates Scheme Certificate Number ENP-036



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications