



Interface® | Composure

SPECIFICATION

Product definition	Tufted Patterned Structured Loop Tile	Style number	30345
Pile Material	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	570 g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
Total Weight	4334g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	2.6 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	6.4 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (EN 986)
Gauge/Ends per 10cm	1/12 - 47.2	Vertical Electrical Resistance	5 x 10 ⁵ Ω >< 1 x 10 ⁸ Ω Computerguard (ISO 10965) (IBM)
Tufts per m2	160,480 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (50 cm x 50 cm ± 0.2%)



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications