


Interface® | Entropy II

SPECIFICATION

Product definition	Tufted Patterned Structured Tip Sheared Tile	Style number	3660300405
Pile Material	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	540 g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Bfl S1 (EN ISO 13501) (NFP 92-506) (PV No. RA 01-304) M3
Total Weight	4404 g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	5.0 mm ± 0.3 mm	Castor Chair Rating	≥2.4 (EN 985)
Total Thickness	7.0 mm ± 0.5 mm	Dimensional Stability	≤0.2% (ISO 2551 / EN 986)
Gauge/Ends per 10cm	1/12 - 47.2	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Tufts per m²	169,920 ± 5%	Colour Fastness - Light	6 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4 m ² (50 cm x 50 cm ± 0.15%)



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications