






Interface® | Fotosfera - Structured

SPECIFICATION

Product definition	Tufted Patterned Structured Loop Tile	Style number	30123
Pile Material	100% BCF Solution Dyed Nylon, 62.5% biobased	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	630g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl S1 (EN ISO 13501)
Total Weight	4640g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	3.9 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	7.7 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551/EN 986)
Gauge/Ends per 10cm	1/12 - 47.2	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965)
Tufts per m²	179,360 ± 5%	Colour Fastness - Light	7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (50 x 50 cm ± 0.15%)


 06
 0336-CPD-8538



 EN 1307



Mission Zero:
 our promise to eliminate
 any negative impact our company
 may have on the environment
 by the year 2020.

www.interface.com