



Interface® | Heuga 530


SPECIFICATION


Product definition	Tufted Plain Textured Loop Tile	Style number	60530
Pile Material	100% BCF Nylon	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	660g/m ² ± 5%	Radiant panel	Euroclass Bfl S1 (EN ISO 9239/1) (EN ISO 13501)
Effective pile yarn weight	400g/m ² ± 10 %	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Total Weight	4309g/m ² ± 7,5%	Castor Chair Rating	≥ 2,4 (EN 985)
Pile Height	3,6 mm ± 0,3 mm	Dimensional Stability	≤ 0,2% (ISO 2551 / EN 986)
Total Thickness	6,8 mm ± 0,3 mm	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Gauge/Ends per 10cm	1/10 - 39.5	Colour Fastness - Light	6-7 (ISO 105/B02)
Tufts per m²	106,650 ± 5%	Tiles per Box	20 - 5 m ² (50 x 50 cm ± 0,2%)
Backing Type	Graphlex®		


CE
06
0336-CPD-8538



Bfl-s1



DS



EN 1307



≤10⁹Ω



Monolithic Quarter Turn



11893



28 dB














33





Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications