



Interface® | Heuga 725

SPECIFICATION

Product definition	Tufted Plain Level Cut Tile	Style number	6072500405
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	720g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Bfl s1 (EN ISO 13501)
Effective pile yarn weight	570g/m ² ± 10%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Total Weight	4330g/m ² ± 5%	Castor Chair Rating	≥ 2,4 (EN 985)
Pile Height	4,3 mm ± 0,3 mm	Dimensional Stability	≤ 0,2% (ISO 2551 / EN 986)
Total Thickness	7,4 mm ± 0,3 mm	Vertical Electrical Resistance	5 x 10 ⁵ Ω >< 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Gauge/Ends per 10cm	1/10 - 41	Colour Fastness - Light	>7 (ISO 105/B02)
Tufts per m2	159,900 ± 7.5%	Tiles per Box	16 - 4 m ² (50 x 50 cm ± 0,2%)
Backing Type	Graphlex®		



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications