

Interface® | Heuga 727 PD

SPECIFICATION

Product definition	Tufted Plain Level Loop Tile	Style number	607273
Pile Material	100% Nylon	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	580 g/m ² ± 10%	Radiant panel	(EN ISO 9239/1) Euroclass Cfl s1 (EN ISO 13501)
Effective pile yarn weight	310 g/m ² ± 10%	Hot Metal Nut Castor Chair Rating	≥ 2,4 (EN 985)
Total Weight	4219 g/m ² ± 5%	Dimensional Stability	≤ 0,2% (ISO 2551 / EN 986)
Pile Height	1.9 mm ± 0.5 mm	Vertical Electrical Resistance	5 x 10 ⁵ Ω >< 1 x 10 ⁹ Ω Computerguard (ISO 10965)
Total Thickness	5.5 mm ± 0.5 mm	Colour Fastness - Light	≥ 6 (ISO 105/B02)
Gauge/Ends per 10cm	1/10 - 39.4	Tiles per Box	20 - 5 m ² (50 x 50 cm ± 0,2%)
Tufts per m²	153660 ± 7.5%		
Backing Type	Graphlex®		

CE
06
0336-CPD-8538

Cfl-s1

DS

EN 1307

Monolithic

Quarter Turn

GUT

35972FB6

23 dB

Performance Profile: Solarex
Certificate Number: ENP-407



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications