

# Interface® | Lima

## SPECIFICATION

<b>Product definition</b>	Tufted Patterned Textured Loop Tile	<b>Style number</b>	<b>3383100405</b>
<b>Pile Material</b>	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	<b>Wear Classification</b>	EN 1307 33 Heavy Contract
<b>Pile Yarn Weight</b>	650g/m <sup>2</sup> ± 5%	<b>Radiant panel</b>	(EN ISO 9239/1) Bfl S1 (EN ISO 13501)
<b>Total Weight</b>	4464g/m <sup>2</sup> ± 5%	<b>Hot Metal Nut</b>	Pass, low radius of effects of ignition (BS 4790)
<b>Pile Height</b>	4.3 mm ± 0.3 mm	<b>Castor Chair Rating</b>	≥ 2.4 (EN 985)
<b>Total Thickness</b>	7.7 mm ± 0.5 mm	<b>Dimensional Stability</b>	≤ 0.2% (ISO 2551 / EN 986)
<b>Gauge/Ends per 10cm</b>	1/12 - 47.2	<b>Vertical Electrical Resistance</b>	5 x 10 <sup>5</sup> Ω >> 1 x 10 <sup>9</sup> Ω Computerguard (ISO 10965) (IBM)
<b>Tufts per m<sup>2</sup></b>	174,640 ± 5%	<b>Colour Fastness - Light</b>	6 (ISO 105/B02)
<b>Backing Type</b>	Graphlex®	<b>Tiles per Box</b>	16 - 4m <sup>2</sup> (50 x 50 cm ± 0.15%)

CE  
06  
0336-CPD-8538  
Bfl-s1  
DS  
EN 1307

Ashlar Quarter Turn  
CEBFAFCD 26dB  
EMS 32802 33  
FM 00679  
Environmental Product Scheme  
Certificate Number ENP 400



**Mission Zero:**  
our promise to eliminate  
any negative impact our company  
may have on the environment  
by the year 2020.

[www.interface.com](http://www.interface.com)

Interface Europe Ltd reserve the right to change or modify specifications