




Interface® | Monochrome



SPECIFICATION

Product definition	Tufted Patterned Structured Loop Tile	Style number	34669
Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	787 g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) Euroclass Bfl s1 (EN ISO 13501)
Total Weight	4714g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height	3.8 mm ± 0.3 mm	Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	8.2 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551/EN 986)
Gauge/Ends per 10cm	1/10 - 39.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Tufts per m²	165,480 ± 5%	Colour Fastness - Light	≥ 7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	16 - 4m ² (50 cm x 50 cm ± 0.2%)



 06
 0336-CPD-8538



Bfl-s1



DS




≤10⁹Ω


EN 1307



 Monolithic



 Pending



 26 dB



 www
















Mission Zero:
 our promise to eliminate
 any negative impact our company
 may have on the environment
 by the year 2020.

www.interface.com

Interface Europe Ltd reserve the right to change or modify specifications