


100%
Recycled
Nylon

Net Effect B603

Interface®



332920 Black Sea




332921 North Sea



332922 Pacific



332923 Arctic



332924 Atlantic



332925 Caspian



332926 Sand



332927 Driftwood





Technical Specifications

Product Definition	Tapestry Tufted Patterned Structured Loop Tile
Konstruktion	Tuftgemusterte strukturierte Schlingenqualität mit Web-Optik
Descripción	Moqueta modular de pelo cortado estructurado/Tapestry
Description	Dalle de moquette à velours tufté structuré à motifs (procédé Tapestry)
Type	Getufted gedessineerde gestructureerde bouclé
Descrizione	Bouclé Tufted Structured Tapestry

Pile Material	100% Recycled BCF Solution Dyed Nylon contains pre and post consumer recycled content
Polfasermaterial	100% recyceltes Polyamid, enthält Anteile pre- und postconsumer recycelten Materials
Composición Fibra	100% Poliamida reciclada BCF tintada en masa con contenido reciclado pre y post consumo
Composition	Fibre polyamide BCF 100% recyclée teint en masse, contenant des éléments recyclés pré et post consommation
Poolmateriaal	100% gerecycled Solution Dyed Polyamide BCF, bevat 100% pre- en post-consumer gerecycled content
Fibra	100% Poliamide BCF riciclata tinta in massa con contenuto riciclato pre- e post -consumer

Pile Yarn Weight / Poleinsatzgewicht / Peso Fibra /	780g/m ² ± 5%
Poids de fibre / Poolinzetgewicht / Peso Felpa	
Total Weight / Gesamtgewicht / Peso Total Poids total /	4755g/m ² ± 5%
Totaalgewicht / Peso Totale	
Pile Height / Polschichtdicke / Altura Fibra /	2,9 mm ± 0,3 mm
Hauteur de la fibre / Poolhoogte / Altezza Felpa	
Total Thickness / Gesamtdicke / Espesor Total /	7,7 mm ± 0,5 mm
Epaisseur totale / Totale dikte / Altezza Totale	
Gauge/Ends 10 cm / Teilung x 10 cm / Galga x 10 cm /	1/10 – 39,4
Jauge-Rangs par 10 cm / Rijen per 10 cm /	
Serraggio x 10 cm	
Tufts per m² / Noppenzahl/m ² / Puntadas m ² /	110,320 ± 5%
Densité du tuft par m ² / Aantal noppen per m ² /	
Densità Punti	
Backing Type / Rückenkonstruktion / Soporte /	Graphlex®
Sous-couche / Ruguitvoering / Sottofondo	
Wear Classification / Beanspruchungsklasse /	Heavy Contract (EN 1307)
Clasificación al tráfico / Classement Gebruiksintensiteit /	Class 33 / LC 1
Resistenza all'usura	

Style	32131
4m ² - 16 tiles per box (50 x 50 cm ± 0,2%)	

Radiant Panel /	(EN ISO 9239/1)
Schwerentflammbarkeit	Euroclass Cfl s1 (EN ISO 13501)
Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Dimensional Stability / Dimensionsstabilität	≤ 0,2% (ISO 2551 / EN 986)

Dimensional Stability / Dimensionsstabilität ≤ 0,2% (ISO 2551 / EN 986)
Estabilidad Dimensional / Stabilité dimensionnelle
Dimensionele stabiliteit / Test Stabilità dimensionale

Sound Absorption					
125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz
0.02	0.04	0.07	0.27	0.33	0.48

[illegible]

Light Values

Product	Colour No	Colour Name	L Value*	Y Value*
Net Effect B603	332920	Black Sea	30.0	6.3
	332921	North Sea	41.0	11.8
	332922	Pacific	25.7	4.7
	332923	Arctic	46.8	15.9
	332924	Atlantic	28.3	5.6
	332925	Caspian	41.0	11.9
	332926	Sand	51.4	19.6
	332927	Driftwood	49.1	17.7

* **Light Value:** L Value = L according to CIE L*a*b* colour space, Y Value = Light Reflectance Value according to BS 8493
Lichtreflexionswerte: L-Wert = L gemäß CIE L*a*b* Farbspektrum, Y-Wert = Lichtreflexionswert gemäß British Standard BS 8493

Valores de Reflectancia de Luz: Valor L= L según CIE L*a*b* espacio de color, Valor Y = Valor de reflectancia de luz según el estándar británico BS 8493

Valeurs concernant la lumière: Valeur L = L faisant référence à la méthode CIE L*a*b* pour la couleur, Valeur Y = Valeurs de réflectance de la lumière selon le British Standard BS 8493

Licht waarden: L Waarde = L volgens CIE L*a*b*kleurruimte, Y Waarde = Licht Reflectie Waarde volgens BS 8493

Indici di riflettanza alla luce: Indice L= L secondo CIE L*a*b* colour space, Indice Y= Indice di riflettanza alla luce secondo la norma BS 8493

Environmental Data Sheet

Construction			
Yarn system	BCF Solution Dyed Nylon (PA6)		
Backing system	Graphlex®		
Recycled Content	Total	Pre Consumer	Post Consumer
Yarn average	100,00%	50,00%	50,00%
Product average	55,32%	47,15%	8,16%
Recycled content can be subject to differences between colours. See details for individual colours on next page.			
Carbon Footprint	Global Warming Potential (kgs CO2 equivalents/sq meter)		
Full life-cycle carbon footprint (following our EPD results or EPD calculation method)	Raw materials and Production:	7.78 kg CO ₂ eq./m²	
	Delivery and installation:	0.70 kg CO ₂ eq./m²	
	Use (10 year):	2.92 kg CO ₂ eq./m²	
	End of life (waste to energy):	8.57 kg CO ₂ eq./m²	
	TOTAL (10 years' lifetime):	19.97 kg CO ₂ eq./m²	
CO ₂ compensation	Carbon neutral Cool Carpet® is standard		
Manufacturing			
Location	Scherpenzeel, NL		
	Factory is certified ISO 14001 since 1996 and ISO 9001 since 1990		
Installation Impacts			
TacTiles™	Optimised for glue-free installation with TacTiles™ connectors with virtually zero VOCs		
Installation Waste	In a typical installation* using the installation method below:		
	Non-Directional – 1-2% installation waste		
	For reference: 2 metre wide broadloom typically generates 7-10 % installation waste		
	* In a rectangular building, installed before walls.		
End-of-life			
Alternatives to landfill	Reuse: Can be cleaned and reused in a non-critical location to extend its useful life		
	Recycling: Can be returned through the Interface ReEntry scheme and be re-used as raw material in new carpet tiles		
	Waste-to-Energy: Can be incinerated in appropriate waste to energy plant		
Indoor Air Quality			
GUT (Gemeinschaft umweltfreundlicher Teppichboden)	The product passes all requirements of GUT's testing criteria regarding hazardous substances, emissions and odour.		
	GUT PRODIS certificate number: BECF885D		
CRI (Carpet & Rug Institute)	Compliant to LEED IQ 4.3 credit (tested in Eurofins to the equivalent test of the CRI Green Label Plus)		
Compliance to Green Building Schemes			
	See next page to check how our products contribute to the main green building certification schemes (BREEAM, LEED, HQE and DGNB)		
Type III Environmental Product Declaration			
EPD according to ISO 14025	This product is covered by the Environmental Product Declaration EPD-IFF-20120019-CBD1-EN		

Recycled content – colour level						
Colourway	Total Recycled Content	Pre consumer recycled content	Post consumer recycled content	Total yarn recycled content	Yarn pre-consumer	Yarn post-consumer
332912 Black Sea	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
332913 North Sea	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
332914 Pacific	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
332915 Arctic	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
332916 Atlantic	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
332917 Caspian	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
332918 Sand	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
332919 Driftwood	55,32%	47,15%	8,16%	100,00%	50,00%	50,00%
Compliance to Green Building Schemes						
BREEAM (UK and international)	BRE Green Guide Ratings: Office - Not Available Education - Not Available Health Care - Not Available Retail (by fashion) - Not Available Potential contribution to following categories and credits: Hea 02 - Indoor air quality – minimising sources of air pollution Hea 05 - Acoustic Performance Mat 01 - Life Cycle Impacts Mat 05 - Designing for robustness Wst 01 - Construction Waste Management					
LEED 2009 US	Potential direct or indirect contribution to following categories and credits: Indoor Environmental Quality Credit 4.1 Low Emitting Materials: Adhesive & Sealants Credit 4.3 Low Emitting Materials: Carpet Systems Materials and Resources Credit 2.1 Construction Waste Management Credit 4.1 Recycled content Credit 5.1 Regional Materials Innovation and Design Credits 1-4 1 Pilot Credit 43, Certified Products					
HQE (FR)	Potential direct or indirect contribution to several points within following targets: 2. Integrated choice of products and construction materials 3. Low site nuisance 9. Acoustic comfort 10. Visual comfort 11. No unpleasant smells 12. Sanitary quality of areas 13. Sanitary air quality					
DGNB (D)	Potential direct or indirect contribution to following criterion ENVIRONMENTAL QUALITY ENV1.2 Local Environmental Impact ECONOMIC QUALITY ECO1.1 Building-Related Lifecycle Costs ECO2.1 Efficient Use of Space SOCIOCULTURAL AND FUNCTIONAL QUALITY SOC1.2 Indoor Air Quality SOC1.3 Acoustic Comfort TECHNICAL QUALITY TEC1.5 Ease of Cleaning and Maintenance TEC1.6 Ease of Dismantling and Recycling					



TacTiles™

- A smarter, more sustainable way to install carpet tiles
- No need for liquid adhesives
- Fitting tiles is quick, clean and easy and the process virtually eliminates emissions
- No damage to sub floors, and nothing to stop you lifting or moving the carpet whenever you want



Entrance Matting

Incredibly tough, hard-wearing and practical; indoor entrance matting acts as the first line of defence to any interior by removing almost 100% of dirt, rain and mud before it's walked into your flooring.

Both of the products in our commercial entrance matting range – Barricade and Foyer – are resilient, functional, easy to maintain and stylish. And it's for these reasons that our barrier matting forms an essential part of any maintenance programme needed to keep your floorcovering looking its very best.