




Interface® | Palette 2000


SPECIFICATION


| | | | |
|--|---|---------------------------------------|--|
| Product definition | Fusion Bonded Plain Level Cut Tile | Style number | 54211 |
| Pile Material | 100% Nylon | Wear Classification | EN 1307 33 Heavy Contract |
| Pile Yarn Weight | 950g/m ² ± 10% | Radiant panel | (EN ISO 9239/1) Euroclass Bfl S1 (EN ISO 13501) |
| Total Weight | 4000g/m ² ± 10% | Hot Metal Nut | Pass, low radius of effects of ignition (BS 4790) |
| Pile Height | 4.8 mm ± 0.3 mm | Castor Chair Rating | ≥ 2.4 (EN 985) |
| Total Thickness | 8.1 mm ± 10% | Dimensional Stability | ≤ 0.2% (ISO 2551/EN 986) |
| Gauge/Ends per 10cm Tufts per m² | 272,000 ± 10% | Vertical Electrical Resistance | 5 x 10 ⁵ Ω >< 1 x 10 ⁹ Ω (ISO 10965) |
| Backing Type | PVC (with high pre-consumer recycled content) | Colour Fastness - Light | ≥ 5 (ISO 105/B02) |
| | | Tiles per Box | 16 - 4m ² (50 x 50 cm ± 0.2%) |



 06
 0338-CPD-1003



 Bfl-s1



 BS



 EN 1307



 ≤10⁹Ω



 Monolithic



 Gut



 71FC45D1



 26 dB



 33













Mission Zero:
 our promise to eliminate
 any negative impact our company
 may have on the environment
 by the year 2020.

www.interface.com