




# Interface® | Polichrome


## SPECIFICATION


<b>Product definition</b>	Tufted Frieze cut pile tile	<b>Style number</b>	<b>60755</b>
<b>Pile Material</b>	100% Nylon	<b>Wear Classification</b>	EN 1307 33 Heavy Contract
<b>Pile Yarn Weight</b>	1050 g/m <sup>2</sup> ± 10%	<b>Radiant panel</b>	(EN ISO 9239/1) Euroclass Bfl S1 (EN ISO 13501)
<b>Total Weight</b>	4800 g/m <sup>2</sup> ± 7.5%	<b>Hot Metal Nut</b>	Pass, low radius of effects of ignition (BS 4790)
<b>Pile Height</b>	4.2 mm ± 0.5 mm	<b>Castor Chair Rating</b>	≥ 2,4 (EN 985)
<b>Total Thickness</b>	7.5 mm ± 0.5 mm	<b>Dimensional Stability</b>	≤ 0,2% (ISO 2551 / EN 986)
<b>Gauge/Ends per 10cm</b>	1/10 - 39.4	<b>Vertical Electrical Resistance</b>	5 x 10 <sup>5</sup> Ω >> 1 x 10 <sup>9</sup> Ω Computerguard (ISO 10965) (IBM)
<b>Tufts per m<sup>2</sup></b>	172,200 ± 5%	<b>Colour Fastness - Light</b>	≥ 7 (ISO 105/B02)
<b>Backing Type</b>	Graphlex®	<b>Tiles per Box</b>	16 - 4m <sup>2</sup> (50 x 50 cm ± 0.2%)


  
 06  
 0336-CPD-8538


  
 Bfl-s1


  
 DB


  
 ≤10<sup>9</sup>Ω


  
 EN 1307


  
 Monolithic


  
 Pending


  
 27 dB


  
 www


  
 Sun


  
 Flooring

  
 Wireless

  
 Buildings

  
 33

  
 Navigation

  
 Scissors



**Mission Zero:**  
 our promise to eliminate  
 any negative impact our company  
 may have on the environment  
 by the year 2020.

[www.interface.com](http://www.interface.com)