

Interface® | Straightforward

SPECIFICATION

Product definition	Microtuft Patterned Level Loop Tile	Style number	3081230005
Pile Material	100% BCF Solution Dyed Nylon contains pre-consumer recycled content	Wear Classification	EN 1307 33 Heavy Contract
Pile Yarn Weight	400g/m ² ± 5%	Radiant panel	(EN ISO 9239/1) CfI S1 (EN ISO 13501)
Total Weight	4179g/m ² ± 5%	Hot Metal Nut	Pass, low radius of effects of ignition (BS 4790)
Pile Height		Castor Chair Rating	≥ 2.4 (EN 985)
Total Thickness	4.8 mm ± 0.5 mm	Dimensional Stability	≤ 0.2% (ISO 2551 / EN 986)
Gauge/Ends per 10cm	5/64 - 50.4	Vertical Electrical Resistance	5 x 10 ⁵ Ω >> 1 x 10 ⁹ Ω Computerguard (ISO 10965) (IBM)
Tufts per m²	176,400 ± 5%	Colour Fastness - Light	7 (ISO 105/B02)
Backing Type	Graphlex®	Tiles per Box	20 - 5m ² (50 x 50 cm ± 0.15%)

06
0336-CPD-8538

www.interface.com



Non-Directional



OBBC9DAE



15dB



EMS 32802



EM 00679



Environmental Product Scheme
Certificate Number ENP-005



red dot design award
winner 2008



material
award



Mission Zero:
our promise to eliminate
any negative impact our company
may have on the environment
by the year 2020.

Interface Europe Ltd reserve the right to change or modify specifications