




# Interface® | Yuton 105


## SPECIFICATION


<b>Product definition</b>	Tufted Patterned Structured Loop Tile	<b>Style number</b>	<b>30558</b>
<b>Pile Material</b>	100% Solution Dyed Nylon	<b>Wear Classification</b>	EN 1307 33 Heavy Contract
<b>Pile Yarn Weight</b>	467 g/m <sup>2</sup> ± 5%	<b>Radiant panel</b>	(EN ISO 9239/1) Euroclass Bfl s1 (EN ISO 13501)
<b>Total Weight</b>	4160g/m <sup>2</sup> ± 5%	<b>Hot Metal Nut</b>	Pass, low radius of effects of ignition (BS 4790)
<b>Pile Height</b>	2.4 mm ± 0.3 mm	<b>Castor Chair Rating</b>	≥ 2.4 (EN 985)
<b>Total Thickness</b>	6.3 mm ± 0.5 mm	<b>Dimensional Stability</b>	≤ 0.2% (EN 986)
<b>Gauge/Ends per 10cm</b>	1/10 - 39.4	<b>Vertical Electrical Resistance</b>	5 x 10 <sup>5</sup> Ω >> 1 x 10 <sup>9</sup> Ω Computerguard (ISO 10965) (IBM)
<b>Tufts per m<sup>2</sup></b>	193,060 ± 5%	<b>Colour Fastness - Light</b>	≥ 7 (ISO 105/B02)
<b>Backing Type</b>	Graphlex®	<b>Tiles per Box</b>	16 - 4m <sup>2</sup> (50 cm x 50 cm ± 0.2%)


  
 06  
 0336-CPD-8538


  
 Bfl-s1


  
 BS


  
 EN 1307


  
 ≤10<sup>9</sup>Ω


  
 Monolithic Ashlar


  
 GUT


  
 25 dB








  
 OC2D92CE













**Mission Zero:**  
 our promise to eliminate  
 any negative impact our company  
 may have on the environment  
 by the year 2020.

[www.interface.com](http://www.interface.com)