

Certification & Testing Information		Magply®
Company information		
<p><u>Manufacturer:</u> IPP Ltd Bradwell Hall Bradwell on Sea Essex CM0 7HX Tel: 0044 (0)1621 776252, Fax: 0044 (0)1621 776688</p>		
Fire Performance		
BS EN 476 (Parts 6&7)*		Class 0
Euroclass EN13501*		A1 (Non-Combustible)
BS EN 476 (Part 22 timber frame)*		Fire Insulation: 86 minutes, Integrity: 91 minutes
BS EN 1364-1:2015 (PIR Timber Frame)*		Fire Insulation: 66 minutes, Integrity: 75 minutes
BS EN 1365-1:2012 (Loaded Wall)*		Fire Insulation: 67 minutes, Integrity: 67 minutes
BS EN 476 (Part 22 spandrel panel)		Fire Integrity: 104 minutes
BS EN 1364-1: 2015 (Steel Frame Partition)		Fire Insulation: 69 minutes, Integrity: 90 minutes
BS EN ISO 1182 Reaction to Fire*		Passed
BS EN 1716 Reaction to Fire*		Passed
Racking Strength		
Nailing Centres	Load per Stud	Racking Resistance to BS 594
150mm/300mm	0 kN	1.74 kN/m
150mm/300mm	5 kN	1.70 kN/m
50mm/150mm	0 kN	5.90 kN/m
Other		
Breathability	EN ISO 12572	0.31MNs/g
Liability		
<p>The information given is correct to the best of our knowledge at the time of publication but without guarantee of accuracy. We do not accept any responsibility for damage and claims arising from handling, transport, storage or disposal of the product. This data sheet applies only to the product named above supplied by IPP. If the product is used as part of other products, information given in the data sheet may be invalidated. E&OE No warranty is hereby expressed or implied.</p>		