



Products Guide 2015



CONTENTS

2	Rolled Lead Sheet
3	Lead Related Products
4	Hard Metal Fabrications
5	Fixings for Lead
6	Restorers for Lead
7	Lead Working Tools
8	Trimlead
9	Lead Motifs

JAMESTOWN COMMITMENT

- **Quality**
- **Service**
- **Stock**
- **Delivery**

Jamestown Metals Limited

Unit B, Bingley Road,
Hoddesdon,
Hertfordshire,
EN11 0NX

Jamestown Metals Limited

11, Naysmith Road South,
Hillington Industrial Estate,
Glasgow,
G52 4RE

T: 01992 801910 F: 01992 801911

Rolled Lead Sheet Theoretical Weights Chart / KG

Width (mm)	Nearest Imperial (inch)	Code 3		Code 4		Code 5		Code 6		Code 7		Code 8	
		3m	6m	3m	6m	3m	6m	3m	6m	3m	6m	3m	6m
150	6	7	13	9	18	11	23	14	27	16	32	18	36
180	7	8	16	11	22	14	27	16	32	19	39	22	43
210	8	9	19	13	26	16	32	19	38	23	45	25	51
240	9	11	22	15	29	18	37	22	43	26	51	29	58
300	12	13	27	18	37	23	46	27	54	32	64	36	72
360	14	16	32	22	44	27	55	32	65	39	77	43	87
390	15	18	35	24	48	30	59	35	70	42	84	47	94
450	18	20	40	28	55	34	69	41	81	48	96	54	109
510	20	23	46	31	62	39	78	46	92	55	109	62	123
600	24	27	54	37	73	46	91	54	108	64	129	72	145
760	30	34	68	47	93	58	116	69	137	81	163	92	184
800	32	36	72	49	98	61	122	72	144	86	171	97	193
850	34	38	76	52	104	65	130	77	153	91	182	103	205
914	36	41	82	56	112	70	139	82	165	98	196	110	221
1000	39	45	90	61	122	76	152	90	180	107	214	121	242
1200	48	54	108	73	147	91	183	108	216	129	257	145	290
1600	63	72	144	98	196	122	244	144	288	171	343	193	386
2400	96	-	-	147	294	183	366	216	433	257	514	290	580
Thickness (mm)		1.32		1.80		2.24		2.65		3.15		3.55	
Kg/m ²		14.97		20.41		25.40		30.05		35.72		40.26	

All theory weights are subject to BS EN12588:06 (manufacturing tolerance of ± 5%), and calculated by: length(m)xwidth(m)xkg/m²



Also available

- Patination Oil
- Flashpoint
- Annular Ring Shank Nails
- Cast Lead Domes
- Lead Weathering Slates
- Flexislates
- Lead Expansion Joints



Also available

- Fixing Clips
- Fixing Strip
- Wood Cored Roll Underlays
- Lead Sheet Restorers
- Solders and Fluxes
- Metwash

Sales Line - 07000 1258806

RELATED PRODUCTS

Underlays

Reduce drag arising from thermal movement; assist against condensation and chemical attack; protect against uneven surfaces.

Building Paper to BS 1521/AF
Geotextiles 220g.m2



Underlays	
OPU0010	25m x 1000mm Geotex
OPU0030	25m x 1000mm Standard A1F
OPU0040	25m x 1000mm Polybit M'top

Wood Cored Rolls

Recommended for detailing and expansion of traditional lead, zinc and copper roofs. Available treated or untreated.

Weathering Slates

Provides a weather-tight joint for flues and soil stacks that penetrate slate, tile, asphalt, felt or lead coverings.
Life expectancy > 20 years.



Wood Cored Roll	
OPW0250	50mm x 2.4m Lead Woodroll Treated
OPW0275	75mm x 2.4m Lead Kingroll Treated
OPW0338	38mm x 2.4m Zinc Woodroll Treated

Flexislates

Code 4 lead vulcanised to a neoprene conical upstand.
Provides a weather-tight joint for flues and soil stacks that penetrate slate, tile, asphalt, felt or lead coverings.
Life expectancy > 20 years.



Weathering Slates	
OPS0230	50mm x 450mm 30° Lead Slate
OPS0245	50mm x 450mm 45° Lead Slate
OPS0290	50mm x 450mm 90° Lead Slate
OPS0330	75mm x 450mm 30° Lead Slate
OPS0345	75mm x 450mm 45° Lead Slate
OPS0390	75mm x 450mm 90° Lead Slate
OPS0430	100mm x 450mm 30° Lead Slate
OPS0445	100mm x 450mm 45° Lead Slate
OPS0490	100mm x 450mm 90° Lead Slate
OPS0530	125mm x 450mm 30° Lead Slate
OPS0545	125mm x 450mm 45° Lead Slate
OPS0590	125mm x 450mm 90° Lead Slate
OPS0630	150mm x 450mm 30° Lead Slate
OPS0645	150mm x 450mm 45° Lead Slate
OPS0690	150mm x 450mm 90° Lead Slate

Expansion Joints

For use with lead lined gutters with restricted falls and as a low cost alternative to the restructuring of existing details.
3m x 260mm
3m x 400mm



Expansion Joints	
OPE0120	Lead 3.0m x 260mm
OPE0130	Lead 3.0m x 400mm
OPE0140	Lead 1.5m x 400mm PLUS



Flexislates	
OPF0015	450mm Code 4 Pitched Lead
OPF0010	450mm Code 4 Flat Lead
OPF0025	450mm Pitched Aluminium Base
OPF0020	450mm Flat Aluminium Base

HARD METAL FABRICATIONS



ROLL TOP RIDGE - 2400mm Long			
Code	Size (inch)	Gauge (swg)	Material
OPY9120	12	10	zinc
OPY9150	12	12	zinc
OPY9155	14	12	zinc
OPY9160	18	12	zinc
OPY9165	12	14	zinc
OPY9170	14	14	zinc
OPY9175	18	14	zinc
OPY9180	12	23	aluminium
OPY9181	14	23	aluminium



VENTED ROLL TOP RIDGE - 2400mm Long			
Code	Size (inch)	Gauge (swg)	Material
OPY9171	14	14	Zinc



COPPER RIDGE & VALLEY - 2000mm Long			
Available in 12" and 14" Please contact our Sales Office on 01226 770110 for further information.			



VALLEY - 2400mm Long			
Code	Size (inch)	Gauge (swg)	Material
OPY0118	12	10	zinc
OPY0130	12	12	zinc
OPY0132	14	12	zinc
OPY0134	18	12	zinc
OPY0133	12	14	zinc
OPY0135	14	14	zinc
OPY0136	18	14	zinc
OPY0205	12	23	aluminium
OPY0206	14	23	aluminium



RIDGE STRAPS			
Code	Size (inch)	Gauge (swg)	Material
OPY9205	12	standard (1.5mm)	galv. mild steel
OPY9210	14	standard (1.5mm)	galv. mild steel
OPY9220	12	heavy duty (3mm)	galv. mild steel
OPY9225	14	heavy duty (3mm)	galv. mild steel

LEAD FIXINGS

Fixing Strip and Clips

Fixings to hold lead secure and to prevent wind lift.
0.6 Copper or 0.4 Stainless Steel.



FIXING STRIP	
OPC1110	50mm x 20m Copper
OPC1210	50mm x 20m T/C Stainless Steel

Hall Clips

Fix flashings up to 20 times faster than with lead wedge. Secure a flashing chase 6 - 18mm.

10 packs per box (50 clips per pack)



FIXING CLIPS	
OPC0110	300mm Copper (10 clips/pk)
OPC0120	600mm Copper (10 clips/pk)
OPC0210	300mm T/C Stainless (10 clips/pk)
OPC0220	600mm T/C Stainless (10 clips/pk)

Flash Point

The only sealant recommended by the Lead Sheet Association! An easy to use, neutral cure, all weather alternative to sand and cement mortar.

When extruded into a 6mm x 12mm joint, will point approx. 5 linear metres.

(12 linear metres in a 5mm x 5mm bead)



Cast Lead Domes

Lead domes complete with brass fixings and washers are ideal for use with intermediate cladding, stone and masonry.

Annular Shank Nails

Copper and Stainless Steel annular ring shank fixings for metal roofing as recommended by trade associations.

HALL CLIPS	
OPC0050	Hallclips (pk of 50)



Annular Shank Nails	
OPN0120	20mm Copper ARS Nails 1kg
OPN0125	25mm Copper ARS Nails 1kg
OPN0130	30mm Copper ARS Nails 1kg
OPN0138	38mm Copper ARS Nails 1kg
OPN0220	20mm S/S ARS Nails 1kg
OPN0225	25mm S/S ARS Nails 1kg
OPN0230	30mm S/S ARS Nails 1kg
OPN0238	38mm S/S ARS Nails 1kg



LEAD SEALANT	
OPM0010	Flashpoint Lead Sealant (310ml tube)



CAST LEAD DOMES	
OPD0001	Cast Lead Dome Set

LEAD RESTORERS

Lead Restorers

Removes dirt and grime to improve, restore and enhance the appearance of lead sheet.

Lead Sheet Cleaner

G1 Lead Sheet Restorer (use with lead <50 years)

G3 Lead Sheet Restorer (use with lead >50 years)



Lead Restorer	
OPR0140	1 litre Lead Sheet Cleaner
OPR0110	1 litre Lead Restorer G1
OPR0130	1 litre Lead Restorer G3

Patination Oil

Designed to aid the prevention of unsightly white staining on newly fixed lead work.

0.5 litre tins - 10 tins per box

1.0 litre tins - 10 tins per box

2.5 litre tins - 4 tins per box



Patination Oil	
OPO0005	0.5 litre (10 per box)
OPO0010	1.0 litre (10 per box)
OPO0025	2.5 litre (10 per box)

Fluxes and solders

Our range of soft solders include...

BSEN 29453: 1994: grades: C, D, G and K.

Our range of fluxes include...

Zinn7, ZD-Pro, Deca-Quartz, Soldering Gel.

METWASH

For the removal of stubborn metal residues from skin.

For use after working with lead and other metals and before eating, drinking or smoking.

500ml bottles - 6 bottles per box.

Advice on use:

Pour a bead of Premium Metwash® Soap and Bodywash onto your hands, work to a lather with warm water or work directly into the skin, cleaning thoroughly all surfaces exposed to the metal and its residue.

Thoroughly dry hands.

Premium Metwash® may be used safely as a hand soap or as an all-over body cleanser.



Metwash	
OPH0005	Metwash 500ml bottle

Lead Funnels



Lead Funnels	
OPZ0050	Funnel 2"
OPZ0055	Funnel 2 1/4"
OPZ0060	Funnel 2 1/2"
OPZ0065	Funnel 2 3/4"

LEAD WORKING HANDTOOLS

Lead Dressers

Small, Medium and Large

Bending Stick

Bossing Stick

Setting Stick

Chase Wedge

Bossing Mallet

Lead Knife

Seaming Pliers

Straight and Cranked

Lead Ladle

Lead Cauldron

Portable Lead Burning Kit

Including Disposable Bottles

Lead Burning Spares



TRIMLEAD

What's so special about Trimlead?

...it's precision cut and ready to use

There's never been a lead flashing like this before!
The Trimlead range includes precision cut fancy designs no hand could equal for detail and consistency. The edges are even and clean, dimensions are stable, and the presentation is immaculate, thanks to extra-tough packaging. Just unroll and get to work! Standard roll size is 3m x 300mm.

...It saves time and money

There's no need to store lead sheet and cut it to shape. Order the quantity you need when you need it, and unpack. You can minimise stockholdings, streamline cashflow. And because all the cutting is done in the factory, there's less need for craft skills on site.

What does Trimlead offer ME?

...Roofing contractors

Trimlead means a faster, 'cleaner' result with less skill and less waste. Just unpack and install'.

...building contractors

Trimlead can be installed quickly and easily, because it's cut to shape. Just trim to length and fix. Waste is almost eliminated, and there's no need to hold large stocks on site.

...architects, designers and specifiers.

Trimlead is a top-quality product which complies with all relevant building standards and has the Jamestown assurance of quality. The range of available designs means that any building can have a flashing that's complementary. Computerised cutting also enables complex designs to be produced if required.

...there's less scrap, less wastage


Trimlead eliminates losses due to cutting to shape. It only has to be trimmed to length. Offcuts can be joined on site or recycled.

...it comes in a range of designs

Trimlead means no more design compromises, precision cutting enables highly complex patterns to be produced as easily as simple ones.

...it's affordable

Trimlead prices are highly competitive, thanks to the investment in advanced production facilities.



Trimlead		
Code	Size	Pattern
OPZ0400	3M x 300mm	Bow
OPZ0410	3M x 300mm	Classic
OPZ0420	3M x 300mm	Norman
OPZ0430	3M x 300mm	Portcullis
OPZ0440	3M x 300mm	Saxon
OPZ0450	3M x 300mm	Shield
OPZ0460	3M x 150mm	Bow
OPZ0461	3M x 150mm	Classic
OPZ0462	3M x 150mm	Norman
OPZ0463	3M x 150mm	Portcullis
OPZ0464	3M x 150mm	Saxon
OPZ0465	3M x 150mm	Shield

LEAD MOTIFS



OPM2001
Lead Wedges (50 pk)



OPM2002
Lead Dot Small



OPM2003
Lead Dot Large



OPM2004
Small Flower Bunch



OPM2005
Cherry Bunch



OPM2006
Fleur De Lys Large



OPM2007
Seahorse



OPM2008
Fish



OPM2009
Large Flower Basket



OPM2010
Grecian Urn



OPM2011
Lion Crest



OPM2012
Sun 9 point



OPM2013
Sun 5 point



OPM2014
Seahorse



OPM2015
Moon



OPM2016
Bow



OPM2017
Fleur De Lys Small



OPM2018
MT15 Lead Dot 1



OPM2019
MT16 Lead Dot 1.25



OPM2020
Bolt



OPM2021
Fern



OPM2022
MT7 Tudor Rose 4.5



OPM2023
MT13 Tudor Rose 2.25



OPM2024
MT17 Tudor Rose 3.5



OPM2025
MT6 Lead Rose 2

Tel : 01992 801910

Fax : 01992 801911

Email : info@jamestownmetals.co.uk

LEAD
ZINC
COPPER
STAINLESS
ALUMINIUM



www.enviro-lead.co.uk