

TECHNICAL SHEET 23.01.02-08-eng



EUROTHERM EPS F-W0

1. Product description

Thermal insulation boards from expanded polystyrene; (CFC free).

2. Technical characteristics

Board format: 1000 x 500 mm

Thicknesses: EUROTHERM F-W0 (from 10 mm to 300 mm)

3. Resistance

Thermal resistance: 80 °C – long-term

4. Conformity

The SIST EN 13163 standard

5. Quality

Quality characteristics of the product are determined by the European standards. For several years, JUB has ensured the achievement of the declared or prescribed level of quality by introducing a system of comprehensive management and quality control ISO 9001, which includes a daily check of quality in our laboratories. In manufacturing the product, we strictly adhere to the European standards in the field of environmental protection and health and safety at work, which is certified by ISO 14001 and OHSAS 18001 certificates.

6. Technical characteristics

CE technical code: EPS-EN 13163-L1-W2-T2-S2-P4-DS(N)2-DS(70,-)1-TR150-BS100

Characteristics	Marking	Description/ data	Unit	Declared	Tolerance	Standard
Length	L	1000	mm	L1	±3	EN 822
Width	W	500	mm	W1	±3	EN 822
Thickness	T	10-300	mm	T1	±2	EN 823
Perpendicularity	S	1000/500	mm	S1	±5	EN 824
Evenness	P	1000/500	mm	P4	±5	EN 825
Dimensional stability	DS	1000/500	%	DS(N)2	±0,2	EN 1603
Pressure strength at 10% def.	CS	-	kPa	-	-	EN 826
Flexural strength	BS	-	kPa	BS100	≥100	EN 12089
Tensile strength perpendicular to the surface	TR	-	kPa	TR150	≥150	EN 1607
Diffusion resistance coefficient	μ	20 - 40	-	-	-	EN 12086
Thermal conductivity coefficient	λ _D	0,039	W/mK	0,039	-	EN 12667
Fire resistance (CE)	-	Euroclass E	-	Euroclass E	-	EN 13501-1
Fire resistance	-	B1	-	B1	-	DIN 4102-1
Density	ρ _a	15-18	kg/m ³	15-18	-	EN 1602

Declared thermal resistance R_D

Characteristic	Marking	Description/data											
Board thickness (mm)	d	10	20	30	40	50	60	70	80	90	100	110	120
Declared thermal resistance (m^2K/W)	R_D	0,25	0,50	0,75	1,05	1,25	1,50	1,80	2,10	2,35	2,60	2,85	3,15
Lambda/thickness ratio (W/m^2K)	$\lambda_{D/d}$	3,90	1,95	1,30	0,98	0,78	0,65	0,56	0,49	0,43	0,39	0,35	0,33
Board thickness (mm)	d	130	140	150	160	180	200	220	240	250	260	280	300
Declared thermal resistance	R_D	3,35	3,55	3,95	4,10	4,60	5,10	5,60	6,15	6,40	6,70	7,20	7,70
Lambda/thickness ratio (W/m^2K)	$\lambda_{D/d}$	0,30	0,28	0,26	0,24	0,22	0,20	0,18	0,16	0,16	0,15	0,14	0,13

7. Areas of application

- As thermal insulation in external thermal insulation composite systems with rendering (ETICS);
- Suitable for new constructions as well as for renovation of buildings;

8. Application

During application, it is required to follow the application instructions and valid professional and legislative regulations.

9. Packaging

Thermal insulation boards are in packages of the size $0.25 m^3$, wrapped up in non-transparent PE-foil. Each package contains a declaration sheet in accordance with the SIST EN 13172 standard.

10. Storage

Store in covered areas, away from sources of heat and fire; do not expose to UV rays; prevent contact with incompatible materials/chemicals.

11. Waste management

The manufacturer ensures that all of its packaging is included into the waste management system (Official Gazette of the RS, No. 84/06 with all changes and amendments).

12. Certificates

Slovenian National Building and Civil Engineering Institute, Dimičeva12, 1000 Ljubljana
 EC Declaration of Conformity with the requirements from the European directive on construction products, which is in line with the European standard EN 13163.

Denomination and date of publishing: **TRC-033/12-zak-lis**, 1 February 2012

JUB kemična industrija d.o.o.
 Dol pri Ljubljani 28, SI-1262 Dol pri Ljubljani, Slovenija
 T: 080 15 56, 01 5884 218 , 01 5884 383
 F: (01) 588 42 50
 E: info@eurotherm-izolacija.si
www.eurotherm-izolacija.si



Proizvod je izdelan v organizaciji, ki je imetnik certifikatov ISO 9001:2008, ISO 14001:2004, OHSAS 18001:2007