

Features

- Concrete Block Paving
- Available in 3 colour finishes
- Lightly textured premium granite aggregate finish
- Various depths available for different traffic loadings
- Normally supplied in a three size mix, single sizes can be obtained separately
- Can be laid in a variety of laying patterns depending on unit size selected



Silver Granite



Black Granite



Buff Granite



Product Range

Dimensions (mm)	Colours	Pcs per m ²	m ² per pack	Pcs per pack	No. of layers per pack	Pack Weight (Kg)
100 x 100 x 60	Silver Granite, Black Granite, Buff Granite	100	8	800	10	1020
3 size x 50	Silver Granite, Black Granite, Buff Granite	35	11.52	403	12	1200
3 size x 60	Silver Granite, Black Granite, Buff Granite	35	9.6	350	10	1205
3 size x 80	Silver Granite, Black Granite, Buff Granite	35	6.72	245	7	1190
200 x 100 x 60	Silver Granite, Black Granite, Buff Granite	50	9.6	480	10	1020
200 x 100 x 80	Silver Granite, Black Granite, Buff Granite	50	6.72	336	7	1115
120 x 160 x 60	Silver Granite, Black Granite, Buff Granite	52	9.6	500	10	1185
160 x 160 x 60	Silver Granite, Black Granite, Buff Granite	40	9	350	10	1125
240 x 160 x 60	Silver Granite, Black Granite, Buff Granite	27	9.6	250	10	1195
120 x 160 x 80	Silver Granite, Black Granite, Buff Granite	52	6.72	350	7	1170
160 x 160 x 80	Silver Granite, Black Granite, Buff Granite	40	6.3	245	7	1045
240 x 160 x 80	Silver Granite, Black Granite, Buff Granite	27	6.72	175	7	1075
200 x 100 x 50	Silver Granite, Black Granite, Buff Granite	50	12.48	576	13	1310
200 x 100 x 60	Silver Granite, Black Granite, Buff Granite	50	9.6	480	10	1060
200 x 100 x 80	Silver Granite, Black Granite, Buff Granite	50	6.72	336	7	1115

Bold text = in stock Light text = Made to order (Minimum order quantity applies).

Technical & Performance Data

Product Type	Concrete Block Paving
Product Standard	BS EN 1338:2003
Manufacturing Method	Hydraulically pressed semi-dry concrete
Finish	Lightly textured granite aggregate finish
Packaging Information	Baled, strapped and plastic cover
Slip/Skid Resistance	Low potential - USRV 65
Strength	Typical tensile splitting strength of $\geq 3,6\text{MPa}$ and a failure load of $\geq 250\text{N/mm}$
Complimentary Products	Kerb sets, Kerb blocks, Tara kerb, Mellifont kerb, Newgrange Setts, Newgrange Flag

Permeable option	Yes, refer to the 'Clima-Pave Brochure'
Application & Trafficking	Product suitable for both pedestrian and car traffic use when installed in conjunction with the correct sub base design. Not suitable for truck / commercial vehicle traffic. For further information on design and loading please see installation standards section on pages 91-93.
Chamfer	No
Joint	Newgrange blocks have a 1.5mm approx. integral spacer nib which will give a resulting standard width of approx. 2mm when laid. Joints should be filled with kiln dried jointing sand – see page 99 for further details on jointing. Note that silver granite kiln dried sand is required for Silver, Buff and Black Granite colour block paving.
BREEAM	'A' rated in accordance with the Green Guide Specification Edition 4, 2009, 'A+' rated when used in conjunction with a prepared recycled sub base.
Certification	ISO 9001:2008 ISO 14001

Get in Touch:

T: +353 1 802 6300 - E: technical@kilsaran.ie - W: www.kilsaran.ie

T: +44 (0)161 872 8899 - E: technical@kilsaraninternational.co.uk - W: www.kilsaraninternational.co.uk

