

Features

- Concrete flag paving
- Elegant ground finish using premium granite aggregate
- Available in 4 colours
- Suitable for use on patios, paths and commercial pedestrian areas
- Can be laid in stack bond or stretcher bond depending on selected unit size(s)



Ground



Silver Granite

Black Granite

Light Granite

Buff Granite

Product Range

| Dimensions (mm) | Colours | Pcs per m ² | m ² per pack | Pcs per pack | No. of layers per pack | Pack Weight (Kg) |
|-----------------|--|------------------------|-------------------------|--------------|------------------------|------------------|
| 450 x 450 x 40 | Silver Granite, Black Granite, Buff Granite, Light Granite | 4.95 | 13.33 | 66 | 11 | 1200 |
| 400 x 400 x 40 | Silver Granite, Black Granite, Buff Granite, Light Granite | 6.25 | 13.44 | 84 | 14 | 1180 |
| 400 x 400 x 50 | Silver Granite, Black Granite, Buff Granite, Light Granite | 6.25 | 10.56 | 66 | 11 | 1170 |
| 600 x 300 x 50 | Silver Granite, Black Granite, Buff Granite, Light Granite | 5.55 | 8.66 | 48 | 8 | 1175 |
| 600 x 400 x 50 | Silver Granite, Black Granite, Buff Granite, Light Granite | 4.16 | 10.56 | 44 | 11 | 1215 |
| 600 x 600 x 50 | Silver Granite, Black Granite, Buff Granite, Light Granite | 2.77 | 10.82 | 30 | 15 | 1180 |
| 400 x 400 x 63 | Silver Granite, Black Granite, Buff Granite, Light Granite | 6.25 | 8.64 | 54 | 9 | 1200 |
| 450 x 450 x 63 | Silver Granite, Black Granite, Buff Granite, Light Granite | 4.94 | 7.26 | 36 | 6 | 850 |
| 400 x 400 x 80 | Silver Granite, Black Granite, Buff Granite, Light Granite | 6.25 | 6.72 | 42 | 7 | 1130 |
| 600 x 400 x 80 | Silver Granite, Black Granite, Buff Granite, Light Granite | 4.16 | 6.72 | 28 | 7 | 1130 |
| 450 x 450 x 50 | Silver Granite, Black Granite, Buff Granite, Light Granite | 4.94 | 10.89 | 48 | 9 | 950 |

Bold text = in stock Light text = Made to order (Minimum order quantity applies).

Technical & Performance Data

| | |
|-------------------------------|--|
| Product Type | Concrete flag paving |
| Product Standard | BS EN 1339:2003 |
| Manufacturing Method | Hydraulically pressed semi-dry concrete |
| Finish | Ground finish |
| Packaging Information | Baled, strapped and plastic cover |
| Slip/Skid Resistance | Medium to low - Typically USRV 52 |
| Strength | Typically class 3 compliant to BS EN 1339:2003 |
| Complimentary Products | Kerb setts, Kerb blocks, Tara kerb, Mellifont kerb |

| | |
|--------------------------------------|--|
| Permeable option | No |
| Application & Trafficking | Product suitable for pedestrian areas and commercial footpaths. For further information on design and loading please see installation standards section on pages 96-98. |
| Chamfer | Standard chamfer of approximately 4mm. Some unit sizes are available with a square edge, please contact the Technical team for more details. |
| Joint | Shelbourne Flags have a 1.5mm approx. integral spacer nib which will give a resulting standard joint width of approx. 2mm when laid. Joints should be filled with Kiln dried jointing sand - see page 99 for further details on jointing. Note that silver granite kiln dried jointing sand is required for Silver and Buff Granite colour flag paving |
| BREEAM | 'A' rated in accordance with the Green Guide Specification Edition 4, 2009. 'A+' rated when used in conjunction with a prepared recycled sub base. |
| Certification | ISO 9001:2008 ISO 14001 |

Get in Touch:

T: +353 1 802 6300 - E: technical@kilsaran.ie - W: www.kilsaran.ie

T: +44 (0)161 872 8899 - E: technical@kilsaraninternational.co.uk - W: www.kilsaraninternational.co.uk

