



Product Service

# CERTIFICATE

No. Z1A 16 07 21662 282

**Holder of Certificate:** Corocord Raumnetz GmbHHolzhauser Str. 139  
13509 Berlin  
GERMANY**Certification Mark:****Product:** Playground equipment  
Spatial network**Tested according to:** DIN EN 1176-1:2008  
EN 1176-1:2008  
DIN EN 1176-11:2014  
EN 1176-11:2014  
AfPS GS 2014:01 PAK

The product meets the safety and health requirements of the German Product Safety Act section 20 to 22 ProdSG. The certification marks shown above can be affixed on the product. It is not permitted to alter the certification marks in any way. In addition the certificate holder must not transfer the certificate to third parties. This certificate is valid until the listed date, unless it is cancelled earlier. See also notes overleaf.

**Test report no.:** 713075921-03\_Rev01**Valid until:** 2021-07-17**Date,** 2016-07-19  
( Harald Bardowicks )

Page 1 of 4





**CERTIFICATE**

**No. Z1A 16 07 21662 282**

**Model(s):** COR- 3028, 3028-2, 3030, 3030-2, 3030-4, 3133, 3140, 3144, 3144-2, 3144-3, 3144-4, 3144-3244, 3233, 3244, 3244-2, 3244-3344, 3348, 3348-2, 3348-4, 3348-3448, 3448, 3448-2, 3458, 3458B

**Parameters:** Spacenets with ropework cells adjoining to form a truncated octahedron, with centre pole and side supports in 1-, 2-, 3- & 4-pole designs with mesh sizes between 28 cm and 58 cm.  
 These pieces of equipment are made of Corocord rope with a diameter from 19-22 mm and 7.5 mm thick membranes made of polyester woven fabric with protective rubber coating.

COR 3028	
L/W/H:	6.30/ 6.30/ 3.85 m
Max. drop height:	1.20 m
COR 3028-2	
L/W/H:	11.96/ 7.36/ 3.85 m
Max. Fallhöhe:	1.20 m
COR 3030	
L/W/H:	7.15/ 7.15/ 3.85 m
Max. drop height:	1.20 m
COR 3030-2	
L/W/H:	15.00/ 10.00/ 3.85 m
Max. drop height:	1.20 m

Futher Parameters see Attachment.

**Factory(ies):** 21662



## Attachment to certificate No. Z1A 16 07 21662 282

COR 3030-4	
L/W/H:	14.00/ 14.00/ 3.85 m
Max. drop height:	1.20 m
COR 3133	
L/W/H:	7.70/ 7.70/ 4.45 m
Max. drop height:	1.35 m
COR 3140	
L/W/H:	9.05/ 9.05/ 5.35 m
Max. drop height:	1.70 m
COR 3144	
L/W/H:	9.95/ 9.95/ 5.80 m
Max. drop height:	1.85 m
COR 3144-2	
L/W/H:	21.30/ 14.00/ 5.80 m
Max. drop height:	1.85 m
COR 3144-3	
L/W/H:	22.25/ 22.25/ 5.80 m
Max. drop height:	1.85 m
COR 3144-4	
L/W/H:	20.10/ 20.10/ 5.80 m
Max. drop height:	1.85 m
COR 3144-3244	
L/W/H:	24.60/ 16.10/ 7.40 m
Max. drop height:	2.15 m
COR 3233	
L/W/H:	9.85/ 9.85/ 5.35 m
Max. drop height:	1.65 m
COR 3244	
L/W/H:	12.35/ 12.35/ 7.40 m
Max. drop height:	2.15 m
COR 3244-2	
L/W/H:	27.95/ 17.90/ 7.40 m
Max. drop height:	2.15 m
COR 3244-3344	
L/W/H:	31.45/ 21.40/ 8.80 m
Max. drop height:	2.40 m



## Attachment to certificate No. Z1A 16 07 21662 282

COR 3348	
L/W/H:	16.20/ 16.20/ 9.30 m
Max. drop height:	2.60 m
COR 3348-2	
L/W/H:	35.90/ 22.90/ 9.30 m
Max. drop height:	2.60 m
COR 3348-4	
L/W/H:	34.60/ 34.60/ 9.30 m
Max. drop height:	2.60 m
COR 3348-3448	
L/W/H:	42.05/ 27.85/ 11.80 m
Max. drop height:	3.00 m
COR 3448	
L/W/H:	19.70/ 19.70/ 11.10 m
Max. drop height:	3.00 m
COR 3448-2	
L/W/H:	46.35/ 27.85/ 11.10 m
Max. drop height:	3.00 m
COR 3458	
L/W/H:	23.65/ 23.65/ 13.00 m
Max. drop height:	3.00 m
COR 3458B	
L/W/H:	23.70/ 23.70/ 13.30 m
Max. drop height:	0.60 m