



Product Specification:

Load Bearing Bar Size	38x7 Tapered
Load Bearing Bar	38 mm ²
Max Clear Span at 3kN/m ²	1015mm
Max Clear Span at 5kN/m ²	885mm
Max Clear Span at 5kN/m ²	865mm with 4mm max deflection
Max Clear Span at 7.5kN/m ²	775mm
Panel Weight	24KG/m ²
Resin	Isophthalic Polyester
Fire Rating	ASTM E84 Class 1<25
Finish	Gritted

Flowdeck solid top moulded GRP grating panels are a lightweight and durable solution for walkways and platforms. The panel is available in a various thickness and has a 3mm solid grip plate to the upper side of the panel. The Isophthalic Polyester Grating panels are suitable for general use where factors such as high-strength, non-conductive, lightweight and corrosion resistant applications are required. Panels are up to 50% lighter than steel. The panels are finished in a hard wearing anti-slip gritted surface – compliant to National and Internationally recognised standards.

Product Colour	Product Code	Pannel Size	Type, Depth & Mesh Size	Resin
LIGHT GREY 7040	FD41000P3A	3.66x1.22Mtr	41mm Solid Gritted Top	Isophthalic Polyester

Quality Assurance

Business Information Modelling (BIM) Level 2 accredited business
 ISO 9001:2015 for Quality Assurance
 ISO 14001:2015 for Environmental procedure
 Certificate of Conformity as standard
 BS4592:2012 / EN141222 : 2016 for Design
 BS4592-0:2006 + A1:2012 for Industrial Flooring & Walkways BS EN 141222-2 2016 Working Platforms & Walkways
 STM E-84 Class 1 (A) : 1998 for Fire Retardency for Surface Spread of Flame
 BS 476 PT 7 Class 2 : 1997 for Fire Retardency
 ASTM D-635 for Self-extinguishing properties

Contact our Sales Department
sales@lk-uk.com +44 (0) 1642 233 299

Contact our Technical Department
technical@lk-uk.com +44 (0) 1642 233 297

Individual calculations sheet available upon request.

The weight is estimated based on a galvanized finish.

Advice and guidance is given in good faith without responsibility.

Calculation sheets must be used from either LK group or other suitably qualified engineering sources to confirm and determine the final max clear span and loading per attached typical data.