

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 1 / 9

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Lithofin TC Classic-Wax

1.2 Relevant identified uses of the substance or mixture and uses advised against

No information available.

1.3 Supplier (manufacturer/importer/only representative/downstream user/distributor)

Distributor :

Casdron Enterprises Ltd.

Street :

Wood End, Prospect Road

Postal code/city :

GB- New Alresford, Hants SO 24 9QF

Telephone :

+44 1962 732126

Telefax :

+44 1962 735373

Contact :

Technical Department
E-mail: sales@lithofin.co.uk

Emergency telephone number:
0196 2732126
(Only available during office hours)

Supplier :

Lithofin AG

Street :

Heinrich-Otto-Str. 36

Postal code/city :

73240 Wendlingen

Telephone :

+49 (0)7024 9403-0

Telefax :

+49 (0)7024 9403-40

Contact :

Technical Department
E-mail: info@lithofin.de

Emergency telephone number:
+49 (0)7024 9403-0
(Only available during office hours)

1.4 Emergency telephone number

see section 1.3

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Directive 67/548/EEC or 1999/45/EC

Flammable. · Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. · Vapours may cause drowsiness and dizziness.

R 10 · N ; R 51/53 · R 67 · R 66

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aquatic Chronic 2 ; H411 - Hazardous to the aquatic environment : Category 2 ; Toxic to aquatic life with long lasting effects.

Flam. Liq. 3 ; H226 - Flammable liquids : Category 3 ; Flammable liquid and vapour.

STOT SE 3 ; H336 - Specific target organ toxicity (single exposure) : Category 3 ; May cause drowsiness or dizziness.

Additional information

This mixture is classified as hazardous according to regulation (EC) No. 1272/2008 [CLP].

Remark

Full text of R-, H- and EUH-phrases: see section 16.

2.2 Label elements

Labelling (67/548/EEC or 1999/45/EC)

Hazard symbols and hazard statements of dangerous substances and preparations



N ; Dangerous for the environment

R-phrases

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 2 / 9

10	Flammable.
51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67	Vapours may cause drowsiness and dizziness.
66	Repeated exposure may cause skin dryness or cracking.

S-phrases

29/35	Do not empty into drains; dispose of this material and its container in a safe way.
61	Avoid release to the environment. Refer to special instructions/safety data sheet.
51	Use only in well-ventilated areas.
24	Avoid contact with skin.

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms



Flame (GHS02) · Environment (GHS09) · Exclamation mark (GHS07)

Signal word

Warning

Hazard statements

H226	Flammable liquid and vapour.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P271	Use only outdoors or in a well-ventilated area.
P310	Immediately call a POISON CENTER/doctor/...
P405	Store locked up.
P501	Dispose of contents/container to

Supplemental Hazard information (EU)

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3 Other hazards

Adverse physicochemical effects

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop. This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe).

2.4 Additional information

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Description

Polishes and wax blends

Hazardous ingredients

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; REACH registration No. : 01-2119458049-33-xxxx ; EC No. : 919-446-0; CAS No. : (64742-82-1)

Weight fraction : 75 - 80 %

Classification 67/548/EEC : R10 N ; R51/53 Xn ; R65 R67 R66

Classification 1272/2008 [CLP] : Flam. Liq. 3 ; H226 Asp. Tox. 1 ; H304 STOT SE 3 ; H336 Aquatic Chronic 2 ; H411

Additional information

All ingredients of this mixture are (pre)registered according to REACH regulation. < 0,1% Benzene, REG(EC) No 1272/2008, Annex VI; J, P

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 3 / 9

4.1 Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Never give anything by mouth to an unconscious person or a person with cramps. Observe risk of aspiration if vomiting occurs.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If unconscious place in recovery position and seek medical advice. In case of respiratory tract irritation, consult a physician.

In case of skin contact

After contact with skin, wash immediately with plenty of water and soap. Immediately remove any contaminated clothing, shoes or stockings. Do not wash with: Cleaning agent, acidic Cleaning agent, alkaline Solvents/Thinner

After eye contact

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Protect uninjured eye.

After ingestion

Call a physician immediately. Keep at rest. Do NOT induce vomiting. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

Self-protection of the first aider

First aider: Pay attention to self-protection!

4.2 Most important symptoms and effects, both acute and delayed

No information available.

4.3 Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water alcohol resistant foam ABC-powder Carbon dioxide (CO₂) Water spray

Unsuitable extinguishing media

Full water jet Strong water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

Carbon monoxide. Carbon dioxide (CO₂)

5.3 Advice for firefighters

Use suitable breathing apparatus.

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Use water spray jet to protect personnel and to cool endangered containers. Do not allow run-off from fire-fighting to enter drains or water courses. Do not inhale explosion and combustion gases.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Use personal protection equipment. Remove all sources of ignition. Provide adequate ventilation. Remove persons to safety. Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction.

6.2 Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For cleaning up

Suitable material for taking up: Universal binder

6.4 Reference to other sections

Safe handling: see section 7 Disposal: see section 13 Personal protection equipment: see section 8

SECTION 7: Handling and storage

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 4 / 9

7.1 Precautions for safe handling

When using do not eat, drink, smoke, sniff.

Protective measures

All work processes must always be designed so that the following is excluded: Inhalation of vapours or spray/mists
Skin contact Eye contact Wear personal protection equipment (see chapter 8). Always close containers tightly after the removal of product. Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. If local exhaust ventilation is not possible or not sufficient, the entire working area must be ventilated by technical means.

Measures to prevent fire

Vapours are heavier than air, spread along floors and form explosive mixtures with air. Keep away from sources of ignition. - No smoking. The product is: Combustible

Fire class : B
Shake before use nein

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed. Keep/Store only in original container.

Hints on joint storage

Storage class (TRGS 510) : 3

Protect from frost nein

Recommended storage temperature 5 - 25 °C

Further information on storage conditions

Keep locked up and out of reach of children. Keep container tightly closed in a cool, well-ventilated place.

7.3 Specific end use(s)

Recommendation

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

DNEL/DMEL and PNEC values

DNEL/DMEL

Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))

Exposure route : Inhalation

Exposure frequency : Long-term (repeated)

Limit value : 71 mg/m³

Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Limit value : 26 mg/kg/d

Limit value type : DNEL/DMEL (DNEL Consumer, Systemic) (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))

Exposure route : Oral

Exposure frequency : Long-term (repeated)

Limit value : 26 mg/kg/d

Limit value type : DNEL/DMEL (Worker, Systemic) (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))

Exposure route : Inhalation

Exposure frequency : Long-term (repeated)

Limit value : 330 mg/m³

Limit value type : DNEL/DMEL (Worker, Systemic) (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))

Exposure route : Dermal

Exposure frequency : Long-term (repeated)

Limit value : 44 mg/kg/d

8.2 Exposure controls

Personal protection equipment

Eye/face protection

Suitable eye protection

Eye glasses with side protection goggles

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 5 / 9

Required properties

DIN EN 166

Skin protection

Hand protection

Suitable gloves type : Gloves with long cuffs

Suitable material : NBR (Nitrile rubber), 0,4mm, >8h; FKM (fluoro rubber), 0,7mm, >8h;

Recommended glove articles : Manufacturer KCL GmbH/Eichenzell-Germany; Ansell/Yarra City-Australia Or comparable articles from other companies.

Additional hand protection measures : Check leak tightness/impermeability prior to use.

Remark : Breakthrough times and swelling properties of the material must be taken into consideration. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Body protection

Protective clothing.

Suitable protective clothing : Chemical protection clothing Chemical resistant safety shoes

Required properties : antistatic.

Recommended protective clothing articles : DIN EN ISO 20345 DIN EN 13034 DIN EN 14605 DIN EN 14404

Remark : Barrier creams are not substitutes for body protection.

Respiratory protection

Usually no personal respirative protection necessary. Respiratory protection necessary at: insufficient ventilation aerosol or mist formation. high concentrations spray application

Suitable respiratory protection apparatus

Combination filtering device (EN 14387) Half-face mask (DIN EN 140) ABEK-P1

Remark

Use only respiratory protection equipment with CE-symbol including four digit test number. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

General health and safety measures

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500. When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes. Remove contaminated, saturated clothing immediately. Wash contaminated clothing prior to re-use. Wash hands before breaks and after work. Apply skin care products after work.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Paste

Colour : light beige

Odour : solvent

Safety relevant basis data

Freezing point :	(1013 hPa)	ca.	47	°C	
Boiling temperature/boiling range :	(1013 hPa)	ca.	140	°C	
Decomposition temperature :	(1013 hPa)		not determined		
Flash point :		ca.	43	°C	closed cup
Ignition temperature :			not determined		
Sustaining combustion			Yes		UN Test L2:Sustained combustibility test
Lower explosion limit :			not determined		
Upper explosion limit :			not determined		
Vapour pressure :	(50 °C)	<	3000	hPa	
Density :	(20 °C)	ca.	0,8	g/cm ³	Pyknometer
Solvent separation test :	(20 °C)	<	3	%	
Water solubility	(20 °C)		immiscible		
pH value :			not applicable		
log P O/W :			not determined		
Flow time :	(23 °C)	>	1000	s	ISO cup 4 mm
Odour threshold :			not determined		
Vapourisation rate :			not determined		
VOC-FR			A+		

9.2 Other information

None

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 6 / 9

SECTION 10: Stability and reactivity

10.1 Reactivity

No information available.

10.2 Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3 Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4 Conditions to avoid

No hazardous reaction when handled and stored according to provisions.

10.5 Incompatible materials

No data available

10.6 Hazardous decomposition products

Does not decompose when used for intended uses.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute effects

Acute oral toxicity

Parameter : LD50 (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))
Exposure route : Oral
Species : Rat
Effective dose : > 15000 mg/kg
Method : OECD 401

Acute dermal toxicity

Parameter : LD50 (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))
Exposure route : Dermal
Species : Rat
Effective dose : 3400 mg/kg
Method : OECD 402

Acute inhalation toxicity

Parameter : LC50 (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))
Exposure route : Inhalation
Species : Rat
Effective dose : 13100 mg/l
Method : OECD 403

Specific symptoms in animal studies

No data available

Irritant and corrosive effects

Assessment/classification

Repeated exposure may cause skin dryness or cracking.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Carcinogenicity

No indication of human carcinogenicity.

Germ cell mutagenicity/Genotoxicity

In vivo mutagenicity

Other information

No experimental indications of in vivo mutagenicity exist.

Human toxicological data

Other information

No indications of human germ cell mutagenicity exist.

Reproductive toxicity

Practical experience/human evidence

No indications of human reproductive toxicity exist.

Overall Assessment on CMR properties

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 7 / 9

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity

Acute (short-term) fish toxicity

Parameter : LC50 (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))
Species : Fish
Effective dose : > 10 mg/l
Exposure time : 96 h
Method : OECD 203

Acute (short-term) daphnia toxicity

Parameter : EC50 (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))
Species : Daphnia
Effective dose : > 10 mg/l
Exposure time : 48 h
Method : OECD 202

Chronic (long-term) daphnia toxicity

Parameter : NOEC (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))
Species : Daphnia
Effective dose : 0,097 mg/l
Exposure time : 21 Tage

Acute (short-term) algae toxicity

Parameter : IC50 (Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), < 0,1 % benzene ; CAS No. : (64742-82-1))
Species : Algae
Effective dose : 4,6 mg/l
Exposure time : 72 h

Effects in sewage plants

Observe local regulations concerning effluent treatment.

12.2 Persistence and degradability

No data available

Biodegradation

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No data available

12.7 Further ecological information

Additional information

The product has not been tested.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Dispose according to legislation.

Product/Packaging disposal

Waste treatment options

Appropriate disposal / Package

Contaminated packages must be completely emptied and can be re-used following proper cleaning. Packing which cannot be properly cleaned must be disposed of.

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 8 / 9

13.2 Additional information

These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use.

SECTION 14: Transport information

14.1 UN number

UN 1993

14.2 UN proper shipping name

Land transport (ADR/RID)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

Sea transport (IMDG)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

Air transport (ICAO-TI / IATA-DGR)

FLAMMABLE LIQUID, N.O.S. (TURPENTINE SUBSTITUTE)

14.3 Transport hazard class(es)

Land transport (ADR/RID)

Class(es) : 3
Classification code : F1
Hazard identification number (Kemler No.) : 30
Tunnel restriction code : D/E
Special provisions : 640E · LQ 5 I · E 1
Hazard label(s) : 3 / N

Sea transport (IMDG)

Class(es) : 3
EmS-No. : F-E / S-E
Special provisions : LQ 5 I · E 1
Hazard label(s) : 3 / N

Air transport (ICAO-TI / IATA-DGR)

Class(es) : 3
Special provisions : E 1
Hazard label(s) : 3

14.4 Packing group

III

14.5 Environmental hazards

Land transport (ADR/RID) : Yes
Sea transport (IMDG) : Yes (P)
Air transport (ICAO-TI / IATA-DGR) : Yes

14.6 Special precautions for user

None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Observe in addition any national regulations!

Water hazard class (WGK)

Class : 2 (Hazardous to water) Classification according to VwVwS

Other regulations, restrictions and prohibition regulations

VOCV-Regulation (CH)

Maximum VOC content (Switzerland) : 75 Wt % according to VOCV

15.2 Chemical Safety Assessment

No information available.

SECTION 16: Other information

16.1 Indication of changes

Safety Data Sheet
according to Regulation (EC) No. 1907/2006 (REACH)

(EN / D)

Trade name : Lithofin TC Classic-Wax

Revision date : 20.02.2015
Print date : 11.06.2015

Version : 0.0.1
Page : 9 / 9

None

16.2 Abbreviations and acronyms

None

16.3 Key literature references and sources for data

None

16.4 Relevant R-, H- and EUH-phrases (Number and full text)

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
R10	Flammable.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65	Harmful: may cause lung damage if swallowed.
R66	Repeated exposure may cause skin dryness or cracking.
R67	Vapours may cause drowsiness and dizziness.

16.5 Training advice

None

16.6 Additional information

None

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.
