



- ✓ **No measuring or troweling needed**
- ✓ **Simple to use in floors, ceilings, and walls**
- ✓ **For use in new construction, remodels, and retrofits**
- ✓ **Trusted by builders, contractors, architects, and DIYers**



Product Description:

Green Glue Noiseproofing Compound is used between two or more sheets of commonly specified building materials such as drywall, plywood, and OSB, to reduce the amount of sound transmission between two rooms. Typical applications are for wall, floor, and ceiling assemblies to reduce airborne and impact noise.

Advantages:

- **Fast** – Quickly applied with no measuring or troweling needed
- **Easy** – Simple to dispense with no specific application pattern necessary
- **Versatile** – For use in new construction, remodels, and retrofits
- **Proven** – Leading manufacturer of soundproofing technologies
- **Trusted** – Used by builders, contractors, architects, and DIYers
- **Multi-Purpose** – For use in walls, ceilings, and floors in a variety of applications
- **Safe** – Independently tested by Underwriters Laboratories for fire safety and environmental impact
- **Effective** – Validated by third-party laboratory testing
- **Sustainable** - Can help achieve LEED Certification

Product Specifications:

Solid Content:	61% +/- 5%
Viscosity:	Light Paste 52,000-56,000cps (#RV-6 @ 10rpm)
Color:	Green
Odor:	Mild, none after drying
Weight:	8.6 +/- 0.5 lbs./gal
Working Time:	15 minutes
Working Temperature:	40°F to 90°F (4°C to 32°C)
Curing Time:	30 days
Coverage:	16-32 sqft per tube / 365-730 sqft per pail
Packaging:	28oz. (828mL) tube / 5 gallon (18.9L) pail
Shelf Life:	One year



It's Green But It's Not Glue!

Green Glue is a viscoelastic compound which transforms annoying energy from sound waves into heat energy that you can't hear.

When sandwiched between two rigid sheets (like Dry Wall) just one layer of Green Glue Noiseproofing Compound can eliminate up to 90% of unwanted noise.

Green Glue is suitable for commercial and domestic new builds and renovations. Application training is minimal. This unique, noise damping compound can be applied in minutes.

It is ready mixed and available in American quart sized tubes, Recommended usage is 2 tubes per board (8ft x 4ft).

Also available in 5 Gallon Pails for larger volumes these pails provide enough compound for 11 8ft x 4ft sheets.

Quart Size Applicators also available from stock.

Floors | Walls | Ceilings

Houses : Flats : Offices : Schools : Hospitals : Hotels
Call 01440 766 975 for Further Information