



Vented soffit slotted to give 25mm continuous ventilation area

Product description

A pioneering concept in roofline solutions. Manufactured from composite aluminium, a material used on some of the world's most prestigious developments, where exceptional durability and aesthetics are key.

- Complements perfectly the long life expectancy and low maintenance of Marley Alutec aluminium gutter and downpipe systems
- Available in both vented and unvented designs
- Installs just like PVC and faster than sheet aluminium systems
- Functional life expectancy of 50+ years with minimal maintenance
- No need for specialist trades or tools. Can be cut, drilled and bent (formed) using standard carpentry skills and tools
- Aluminium is a sustainable material, infinitely recyclable and responsibly sourced

Product Sizes

Code	Depth A (mm)*	Nominal length (m)
FV1100	100	3
FV1180	180	3
FV1240	240	3
FV1365	365	3
FV1490	490	3
FV1740	740	3

* Non standard sizes available on request

Physical properties

Material	4mm thick aluminium composite. Polyethylene thermal break between external surfaces
Finish	Kynar 500 fluorocarbon PVDF paint system

Functional Life Expectancy

Marley Alutec aluminium eaves solutions have a functional life-expectancy of 50+ years with minimal maintenance. All products are manufactured using only marine grade aluminium and coated with PVDF external architectural grade paint.

- Clause:** H72/470
Product: Aluminium composite soffit system
Manufacturer: Marley Alutec, Unit 1 (G-H), Hudson Road, Elms Farm Industrial Estate, Bedford MK41 0LZ.

Product information

Visit www.marleyalutec.co.uk or click on the individual links below.

Technical Services Department

Marley Alutec Technical Services Department has many years' experience in assisting specifiers with all aspects of drainage design and installation. For advice, contact them on technical@marleyalutec.co.uk, 01234 359438

Standards

All Marley Alutec systems are manufactured to and in excess of the appropriate BS or EN Standards. For a full list download the range brochure in the **Product information** section.

Maintenance

To maximise the life of the decorative paint finishes, all parts should be washed down with clean water at least every 12 months. This period would be shortened to 6 months in a marine/aggressive environment.

Environmental

Marley Alutec is committed to continually reducing its environmental impact and is accredited to ISO 14001:2004.



Handling & storage

All goods should be stored under cover to protect against ingress of water between surfaces of composite aluminium sheets. Flat panels should be stored fully supported on a flat surface. Profiled lengths should also be fully supported throughout the product length and appropriately stacked to avoid damage to the profile. Ensure that the self-adhesive peel off protective cover is not damaged during handling exposing the painted surface to potential damage.



evolve RAINWATER SYSTEMS



traditional RAINWATER SYSTEMS



aligator RAINWATER SYSTEMS



evolve FASCIA, SOFFIT & COPING



elite ROOF OUTLET SYSTEMS

ALUTEC

ALUMINIUM RAINWATER SYSTEMS

Head office

For general enquiries, please call **01234 359438**
For technical enquiries please call **01234 344108**
email: enquiries@marleyalutec.co.uk
Fax: **01234 357199**

Unit 1 (G-H), Viking Industrial Park, Hudson Road,
Elms Farm Industrial Estate, Bedford MK41 0LZ

Export Division

Aliaxis UK
Dickley Lane, Lenham, Kent, ME17 2DE
Telephone: **01622 858888** Fax: **01622 850778**



an *Aliaxis* company

[f](#) /marleyalutec
[t](#) @marleyalutec
[in](#) /company/marleyalutec
marleyalutec.co.uk