

TECHNICAL GUIDE FULLY REVERSIBLE WINDOW



A



Deceuninck's new Fully Reversible Window (FRW) is best-in-class for security, weather and thermal performance. It makes life easier for installers, fabricators and specifiers.

Designed for tower blocks, social housing,

hospitals, care homes and any other commercial projects where cleaning the outside safely from the inside is the only option.

With a 1.4mx1.4m maximum aperture it is perfect for modern architecture.


deceuninck

Deceuninck Limited

Stanier Road • Porte Marsh Industrial Estate • Calne • Wiltshire SN11 9PX
T 01249 816 969 • F 01249 815 234
deceuninck.ltd@deceuninck.com • www.deceuninck.co.uk


December 2015

Document No:
82126-8104
Fully Reversible Window



Weather test results

	Size Tested	1.4 x 1.4
Air Permeability	Class	A4
	Rating	600 Pa
Water tightness	Class	9A
	Rating	E 1050 Pa
Wind Resistance	Class	A5
	Rating	AE 2400 Pa




U-Values

4/20/4 Argon Cavity		4/14/4/14/4 Argon Cavity	
U_g 1.219	U_g 1.070	U_g 0.683	U_g 0.591
U_w 1.4	U_w 1.3	U_w 1.0	U_w 0.96

WER's


4/20/4 Argon Cavity	4/14/4/14/4 Argon Cavity
A0	A+ 15





Stock Colours

- Available from stock
- Beautiful authentic 'wood like' finish
- Extremely durable
- 10 year manufacturer's guarantee
- All available on white



All Colours

- Available on a short lead time

