



KEY:

- ① NORDAN HIGH PERFORMANCE INWARD OPENING DOOR ALUMINIUM CLAD
- ② SEALED GLAZING UNIT
- ③ GLAZING SYSTEM - THE SYSTEM IS SELF VENTILATING AND SELF DRAINING, THEREFORE NO MOISTURE IS IN CONTACT WITH THE WOOD. TO IMPROVE SECURITY, THE SEALED UNIT IS GLUED INTO THE SASH
- ④ VACUUM IMPREGNATED TIMBER - NORDAN PRODUCTS USE TIMBER SOURCED FROM SUSTAINABLE FORESTS, WITH PEFC FULL CHAIN OF CUSTODY. VACUUM IMPREGNATION PROTECTS THE TIMBER FROM ROT, FUNGAL AND INSECT ATTACK.
- ⑤ ALUMINIUM GLAZING BEADS - ALUMINIUM GLAZING BEADS REDUCE THE LEVEL OF MAINTENANCE AND CREATE A MORE SUBSTANTIAL DESIGN BY ALLOWING FULL VENTILATION AND DRAINAGE. THE ALUMINIUM IS SECURELY CLIPPED INTO PLACE THUS PREVENTING AND DAMAGE TO THE FRAME
- ⑦ GASKET - THE PROFILE OF THE DOOR SECTIONS AND DESIGN FOR DRAINAGE DEPENDS ON THE WEATHER SEAL BEING ABLE TO PROVIDE THE REQUIRED RESISTANCE OF THE GAP BETWEEN SASH AND FRAME TO WEATHER
- ⑧ OPTIONAL ALUMINIUM CLADDING - THE OPTIONAL ALUMINIUM RAIN SCREEN CLADDING GREATLY IMPROVES THE LIFE-SPAN OF THE PRODUCT AND VASTLY REDUCES MAINTENANCE COSTS. IT CAN ALSO BE POWDER COATED TO ANY RAL COLOUR OF YOUR CHOICE

- ⑨ INSULATED DOOR REVEAL
- ⑩ AIR TIGHTNESS TAPE AND SEALANT APPLIED TO BACK OF FRAME & RETURNED ONTO TIMBER KIT
- ⑪ COMPRESSIBLE FILL & SHIMS AS REQUIRED
- ⑫ SEALANT AT DOOR FRAME
- ⑬ TIMBER FRAME KIT IN ACCORDANCE WITH ACCREDITED CONSTRUCTION DETAILS (SCOTLAND) 2010
- ⑭ 100mm THICK DENSE CONCRETE BLOCKWORK OUTER LEAF WITH ROUGHCAST FINISH (OUTER LINTOL)
- ⑮ 50mm CAVITY
- ⑯ CAVITY BARRIER FITTED TO TIMBER FRAME 38 x 48mm SITE FIXED, ISOLATED FROM TIMBER BLOCKWORK BY DPC (NOTE CAVITY BARRIER CAN BE FACTORY FITTED TO DOORS BY NORDAN ON REQUEST, DPC SUPPLIED BY OTHERS. SCREWS AT 600mm CENTRES TO BE CONFIRMED IN ENGINEERS SPECIFICATION
- ⑰ DPC ACROSS CAVITY AS CAVITY TRAY. TAKEN IN UNDER BREATHER PAPER
- ⑱ STAINLESS STEEL FIXING STRAP, BENT ACROSS & FIXED TO TIMBER KIT - ALL WITH SUITABLE FIXINGS PER STRUCTURAL ENGINEER'S RECOMMENDATIONS
- ⑲ OUTER BREATHER PAPER LAPPED WITH INNER VAPOUR BARRIER AT UNDERSIDE OF LINTOL. SS FIXING STRAPS (18) FITTED (UNLESS FIXIED VIA FIRESTOPS) & THEN AIR TIGHTNESS TAPE (10) FITTED

DESIGN ADVICE

DRAWING TO BE READ IN CONJUNCTION WITH NORDAN MEASURING & INSTALLATION LEAFLET. AVAILABLE AT www.nordan.co.uk/uk/downloads

ALL DETAILS ARE SUBJECT TO CHANGE BY PROJECT INSURER / CERTIFIERS LATEST REQUIREMENTS i.e NHBC

ALL DETAILS ARE SUBJECT TO CHANGE BY TIMBER FRAME KIT MANUFACTURERS REQUIREMENTS

ALL DETAILS MUST BE READ IN CONJUNCTION WITH THE LATEST ACCREDITED CONSTRUCTION DETAILS (SCOTLAND) & ALTERED ACCORDINGLY TO ENSURE AIR TIGHTNESS & THERMAL CONTINUITY

AIR TIGHTNESS GENERAL NOTES

- INSTALL DOOR TO OVERLAP WITH OUTER LEAF OF WALL FINISH
- INSTALL AIR TIGHTNESS SEAL BETWEEN THE INSIDE FACE OF THE DOOR AND THE STRUCTURAL FINISH OF THE DOOR OPENING

THERMAL CONTINUITY GENERAL NOTES

- CHECK THAT THERE IS NO DEBRIS IN THE CAVITY
- INSTALL CAVITY BARRIER AROUND OPENING

TITLE:	INWARD DOOR HEAD DETAIL
DATE:	MAY 2011
SCALE:	1:2 @ A3
DWG NO:	NDUK ID 023



© 2010 NorDan AS



www.nordan.co.uk

Door Head Detail

Scale 1:2

Timber Frame Kit with outer Blockwork cladding