



POLISH

Solvent-based emulsion care product especially for wood flooring

Description:

Solvent-based emulsion care product for high-quality maintenance of wooden flooring.

Especially suitable for the surface cleaning of:

- Sealed wood flooring
- Sealed cork flooring
- Impregnated wood flooring
- Floorboards
- Woodblocks

Product Properties / Benefits:

Solvent-based emulsion care product that gives long-term protection to the floor seal by means of a protective film and thereby prevents traffic- and heel- marks. Polish extends the wear life of the lacquer.

- Ready to use
- Hard wearing
- Formaldehyde-free

Technical Data:

Packaging:	metal canister/bottle
Packsize:	1 litre
Shelf life:	approx. 24 months
Colour:	teal
Working temperature:	18 – 25 °C
Solvent content:	approx. 80 %
Consumption:	approx. 30 ml/m ²
Coverage per litre:	30 – 50 m ²
Ready for polishing:	after 10 minutes*

*Under normal climatic conditions.



PALLMANN

POLISH

Surface Preparation:

Using a mop, soft brush or vacuum cleaner, with Pallmann CLEANER as required, ensure that the floor is free from dirt, dust, grease, oil or wax (old wax).

Application:

1. Before use, allow the container to come to room temperature and shake well.
2. Apply a thin and even coat of Pallmann POLISH using the Pallmann WASH-MOP.
3. After approx. 10 minutes, the treated surface must be polished. We recommend the use of a rotary polishing machine with a white pad.
4. So as not to exceed the drying time, large areas must be divided into sections of 30 – 50 m². Too long a drying time results in streaks.
5. Regular maintenance increases the wear life; with Pallmann POLISH, the surface receives optimum protection and the appearance is maintained.
6. Clean the Wash-Mop with Pallmann a suitable thinner; if the Wash-Mop is soaked in Pallmann POLISH, there is a risk of spontaneous combustion.

Important Notes:

- Shelf life minimum 24 months in original packaging when stored in constant conditions. Tightly reseal opened containers.
- Optimum conditions are 18 to 25 °C and relative humidity < 65 %. Low temperatures and high humidity lengthen, high temperatures and low humidity shorten the drying time.
- Do not exceed the drying time as this will lead to streaking.
- When applying with a rotary machine, apply a few drops of POLISH and distribute with a white pad. After a minimum of 15 minutes, polish off with a clean white pad.
- Freshly sealed surfaces must be left until after final strength is achieved (depending on the type of seal system) before maintaining with Pallmann POLISH.
- For deep cleaning of heavily soiled or over-waxed flooring, use Pallmann Deep-Cleaner.
- On a surface of around 2 – 4 m², allow the Deep-Cleaner to work for 2 – 5 minutes, release the dissolved material with a scrubbing brush and remove with cloths. Then rinse twice with clean, lukewarm water and wipe the floor dry.
- All deep-cleaned surfaces must be re-treated; the best care and protection is guaranteed with Pallmann POLISH.

Protection of the Workplace and the Environment:

High solvent content. Flammable. Solvents in this product may form explosive air-vapour-mixture. Vapours may be harmful to health. Therefore provide good ventilation during and after use. No smoking, no open flames. Do not inhale vapours. Switch off all electric devices like door-bells, refrigerators, electric stoves, etc. Use barrier cream and protective gloves. Observe safety information on product label as well as safety data sheet

Disposal:

Where possible, collect product residues and re-use. Do not allow into drains, water courses or landfill. Empty, drip-free plastic or metal containers are recyclable. Containers with liquid residues and liquid waste product are Special Waste. Containers with hardened residues are Construction Waste.

The above information is based on our experience and careful investigations. The variety of associated materials and different construction and working conditions cannot be individually checked or influenced by us. The quality of your work depends, therefore, on your own professional judgement and product usage. If in doubt, conduct a small test or obtain technical advice. Observe the installation recommendations of the covering manufacturer.

The publication of this Product Data Sheet invalidates all previous product information. The respective updated version of this datasheet can be found on our homepage under www.pallmann.net

