


maestro38

Compose your setting in tune with one of our most popular premium range carpets




heavy contract
38 colourways






Auburn Falls
LRV (L48.02 Y16.83)



Azure Fusion
LRV (L31.34 Y6.81)



Beige
LRV (L49.41 Y17.94)



Blue Diamond
LRV (L42.55 Y12.87)



Deep Blue
LRV (L18.83 Y2.72)



Delhi Bazaar
LRV (L31.41 Y6.85)




Dublin Bay
LRV (L36.28 Y9.18)




Dusky Pink
LRV (L29.33 Y5.97)



Bracken Salts
LRV (L51.08 Y19.35)



Brooklyn Nights
LRV (L? Y?)




Celestial Blue
LRV (L38.42 Y10.34)



Charcoal
LRV (L20.25 Y3.05)



Earth Glaze
LRV (L49.77 Y18.24)



Emerald Orchestra
LRV (L36.45 Y9.26)



Gold
LRV (L54.24 Y22.17)



Hot Paprika
LRV (L35.55 Y8.79)




Claret
LRV (L24.19 Y4.16)




Cocoa Blush
LRV (L29.21 Y5.94)



Coral
LRV (L46.29 Y15.53)



Dark Green
LRV (L23.5 Y3.95)



Indian Ivy
LRV (L50.06 Y18.47)



Night Jewel
LRV (L? Y?)



Nutshell
LRV (L54.48 Y22.44)



Red
LRV (L28.10 Y5.50)




Royal Regetta
LRV (L21.44 Y3.36)



Sapphire
LRV (L30.46 Y6.43)



Silver
LRV (L41.43 Y12.15)




Steel
LRV (L29.05 Y5.88)



Sunflower
LRV (L42.38 Y?)




Sycamore
LRV (L29.94 Y6.22)



Teal
LRV (L36.39 Y9.23)



Turquoise
LRV (L33.45 Y7.76)



Twilight
LRV (L? Y?)



Velvet Truffle
LRV (L39.56 Y10.99)




Volcanic Splash
LRV (L33.9 Y7.96)



Woodland Fern
LRV (L47.59 Y16.47)



Gunmetal
LRV (L24.58 Y4.29)



Terracotta
LRV (L30.54 Y6.47)

Suitable for offices,
retail, schools,
colleges and leisure

Heavy contract

10 year warranty

Available in plain
cutpile tile

38 colourways

Up to 55% recycled
content in the
bitumen backing



Style
1/10" gauge Tufted Cut Pile Tile



Yarn Construction
100% Antron Nylon



Pile Yarn Weight
1050 gsm



Pile Height
5mm



Pile Density
181,102 tufts per m2



Total Weight
4955 gsm (Tile)



Total Thickness
8mm (Tile)



Backing
Bitumen Backed



Dimensions
50cm x 50cm



Wear Classification
Heavy Contract



Anti-static
< 2kV body voltage
Suitable for use with computers



Colour Fastness
To Light (ISO105 – B02) > 5
To Water (ISO 105 - E01) > 4
To Rubbing (ISO 105 - X12) > 4



Flammability
Flammability (BS5287) Assessment and labelling
of Textile Floorcoverings tested to BS4790
Low radius of Char
(Hot Metal Nut Test) CE Flam rating - Bfl-s1



Castor Chair Test
BS EN 985
r value 2.8 continuous use

INSTALLATION

Sub floors should be clean, dry and flat and prepared in accordance with BS5325. Timber floors should be covered with plywood or other appropriate sheet materials. For tiles use F Ball tackifier F41 or Laybond 79. Tiles may be laid tessellated. Tiles should be allowed to condition for a minimum of 24 hours at the expected temperature and humidity prevailing when the building is in use. Further installation information is available from the Paragon Sales Office.

COLOUR

For technical reasons, as with all textile materials, it may not be possible to colour match from different batches. Orders requiring colour match should be placed at the same time. Production may therefore show variations to the sample card.

MAINTENANCE

It is recommended that a maintenance schedule be initiated from the date of installation to achieve maximum life expectancy of the product. Regular vacuum cleaning with a twin motored upright vacuum cleaner is essential. All spillages and stains should be attended to immediately. For detailed information, please consult the Paragon cleaning and maintenance guide. It is imperative that all internal carpets are well protected from outside soiling and moisture by the use of barrier matting such as MatWorks, also available from Paragon.





Farfield Park
Manvers
Wath-upon-Dearne
Rotherham, S63 5DB.

T. +44 (0) 1709 763 839
F. +44 (0) 1709 763 813
E. sales@paragon-carpets.co.uk
W. www.paragon-carpets.co.uk

