

strobe

Cutting edge Linear design for contemporary schemes

heavy contract
8 colourways plus 1





Fusion Grey Accent
Colour
(LRV - L25.79 Y4.69)



Flex 2620
(LRV - L26.23)



Blaze 2604
(LRV - L24.35 Y4.24)



Extreme 2606
(LRV - L26.83 Y5.11)



Ignite 2603
(LRV - L29.02 Y6.09)



Spark 2621
(LRV - L25.36 Y4.57)



Rapid 2614
(LRV - L28.12 Y5.53)



Force 2605
(LRV - L31.78 Y7.47)



Plasma 2619
(LRV - L24.81 Y4.39)



Suitable for office, commercial, retail, schools, colleges and leisure

Heavy Contract

10 Year Warranty

Available in 8 linear designed colourways + 1 Grey Accent Colour

610 gsm (Grey Fusion 580gsm) Pile Yarn Weight

Up to 55% of the total product is recycled content

S Style
1/10" gauge

F Yarn Construction
100% Solution Dyed Nylon / Space Dyed Nylon

P Pile Yarn Weight
610 gsm (Grey Fusion 580gsm)

H Pile Height
3.5mm

T Total Weight
4390 gsm (Tile)

T Total Thickness
6mm (Tile)

B Backing
Bitumen Backed

W Wear Classification
Heavy Contract

AS Anti-static
< 2kV body voltage
Suitable for use with computers

CF Colour Fastness
To Light (ISO105 – B02) > 6
To Water (ISO 105 - E01) > 5
To Rubbing (ISO 105 - X12) > 5dry 4-5 wet

FL Flammability
Flammability (BS5287) Assessment and labeling of Textile Floor coverings tested to BS4790
Low radius of Char
(Hot Metal Nut Test) CE Flam rating - Bfl-s1

CC Castor Chair Test
BS EN 985 continuous use

10 Warranty
10 Years

INSTALLATION

Sub floors should be clean, dry and flat and prepared in accordance with BS5325. Timber floors should be covered with plywood or other appropriate sheet materials. For tiles use F Ball tackifier F41 or Laybond 79. Tiles may be laid tessellated or broadloom. Tiles should be allowed to condition for a minimum of 24 hours at the expected temperature and humidity prevailing when the building is in use. Always use seam sealer if an impermeable finish is required. Further installation information is available from the Paragon Sales Office.

COLOUR

For technical reasons, as with all textile materials, it may not be possible to colour match from different batches. Orders requiring colour match should be placed at the same time. Production may therefore show variations to the sample card.

MAINTENANCE

It is recommended that a maintenance schedule be initiated from the date of installation to achieve maximum life expectancy of the product. Regular vacuum cleaning with a twin motored upright vacuum cleaner is essential. All spillages and stains should be attended to immediately. For detailed information, please consult the Paragon cleaning and maintenance guide. It is imperative that all internal carpets are well protected from outside soiling and moisture by the use of barrier matting such as MatWorks, also available from Paragon.



paragon

CARPETS

Farfield Park
Manvers
Wath-upon-Dearne
Rotherham, S63 5DB.

T. +44 (0) 1709 763 839
F. +44 (0) 1709 763 813
E. sales@paragon-carpets.co.uk
W. www.paragon-carpets.co.uk