

NBS SPECIFICATION; Workspace Linear

M50 RUBBER/PLASTICS/CORK/LINO/CARPET/TILING/SHEETING CARPET TILING.

MANUFACTURER: -PARAGON, A Division of National Floor Coverings Ltd. Farfield Park, Manvers, Wath upon Dearn, Rotherham, S63 5DB, tel 0845 601 0431

Workspace Linear CARPET TILES

A tufted loop pile carpet tile manufactured from solution dyed / space dyed nylon , 1/10" gauge

Available in 15 colourways and carries a Class 4 Heavy Contract Rating

The 6.5mm thick tile is available in 500 x 500mm . Size options are available with minimum quantities.

B.S. 14001

Consult with Paragon for technical literature and to obtain samples

Product Reference: - PARAGON Workspace Linear

TYPE: Tufted loop pile tile

BS 1307 Classification

Category: N

LEVEL OF USE: 4

Size 500 x 500mm

15 colours available

Method of laying: BS5325 Loose Lay after acclimatization for 24 hours. For underfloor heating application, heater must be turned off for a minimum of 48 hours prior to laying and after laying brought up to operating temperature in flow increments, over a 48 hours period.

Adhesive: - F. Ball's, F41 or Similar .

Warranties. 10 Year Bitumen Tile